

Network Working Group
Request for Comments: 1067

J. Case
University of Tennessee at Knoxville
M. Fedor
NYSERNet, Inc.
M. Schoffstall
Rensselaer Polytechnic Institute
J. Davin
Proteon, Inc.
August 1988

A Simple Network Management Protocol

Table of Contents

1. Status of this Memo	2
2. Introduction	2
3. The SNMP Architecture	4
3.1 Goals of the Architecture	4
3.2 Elements of the Architecture	4
3.2.1 Scope of Management Information	5
3.2.2 Representation of Management Information	5
3.2.3 Operations Supported on Management Information	6
3.2.4 Form and Meaning of Protocol Exchanges	7
3.2.5 Definition of Administrative Relationships	7
3.2.6 Form and Meaning of References to Managed Objects ..	11
3.2.6.1 Resolution of Ambiguous MIB References	11
3.2.6.2 Resolution of References across MIB Versions.....	11
3.2.6.3 Identification of Object Instances	11
3.2.6.3.1 ifTable Object Type Names	12
3.2.6.3.2 atTable Object Type Names	12
3.2.6.3.3 ipAddrTable Object Type Names	13
3.2.6.3.4 ipRoutingTable Object Type Names	13
3.2.6.3.5 tcpConnTable Object Type Names	13
3.2.6.3.6 egpNeighTable Object Type Names	14
4. Protocol Specification	15
4.1 Elements of Procedure	16
4.1.1 Common Constructs	18
4.1.2 The GetRequest-PDU	19
4.1.3 The GetNextRequest-PDU	20
4.1.3.1 Example of Table Traversal	22
4.1.4 The GetResponse-PDU	23
4.1.5 The SetRequest-PDU	24
4.1.6 The Trap-PDU	26
4.1.6.1 The coldStart Trap	27
4.1.6.2 The warmStart Trap	27
4.1.6.3 The linkDown Trap	27
4.1.6.4 The linkUp Trap	27

Case, Fedor, Schoffstall, & Davin

[Page 1]

□

RFC 1067

SNMP

August 1988

4.1.6.5 The authenticationFailure Trap	27
4.1.6.6 The egpNeighborLoss Trap	27
4.1.6.7 The enterpriseSpecific Trap	28
5. Definitions	29
6. Acknowledgements	32
7. References	33

1. Status of this Memo

This memo defines a simple protocol by which management information for a network element may be inspected or altered by logically remote users. In particular, together with its companion memos which describe the structure of management information along with the initial management information base, these documents provide a simple, workable architecture and system for managing TCP/IP-based internets and in particular the Internet.

This memo specifies a draft standard for the Internet community. TCP/IP implementations in the Internet which are network manageable are expected to adopt and implement this specification.

Distribution of this memo is unlimited.

2. Introduction

As reported in RFC 1052, IAB Recommendations for the Development of Internet Network Management Standards [1], the Internet Activities Board has directed the Internet Engineering Task Force (IETF) to create two new working groups in the area of network management. One group is charged with the further specification and definition of elements to be included in the Management Information Base (MIB). The other is charged with defining the modifications to the Simple Network Management Protocol (SNMP) to accommodate the short-term needs of the network vendor and operations communities, and to align with the output of the MIB working group.

The MIB working group has produced two memos, one which defines a Structure for Management Information (SMI) [2] for use by the managed objects contained in the MIB. A second memo [3] defines the list of managed objects.

The output of the SNMP Extensions working group is this memo, which incorporates changes to the initial SNMP definition [4] required to attain alignment with the output of the MIB working group. The changes should be minimal in order to be consistent with the IAB's directive that the working groups be "extremely sensitive to the need to keep the SNMP simple." Although considerable care and debate has gone into the changes to the SNMP which are reflected in this memo,

Case, Fedor, Schoffstall, & Davin

[Page 2]

□

RFC 1067

SNMP

August 1988

the resulting protocol is not backwardly-compatible with its predecessor, the Simple Gateway Monitoring Protocol (SGMP) [5]. Although the syntax of the protocol has been altered, the original philosophy, design decisions, and architecture remain intact. In

order to avoid confusion, new UDP ports have been allocated for use by the protocol described in this memo.

Case, Fedor, Schoffstall, & Davin

[Page 3]

□

RFC 1067

SNMP

August 1988

3. The SNMP Architecture

Implicit in the SNMP architectural model is a collection of network management stations and network elements. Network management stations execute management applications which monitor and control network elements. Network elements are devices such as hosts, gateways, terminal servers, and the like, which have management agents responsible for performing the network management functions

requested by the network management stations. The Simple Network Management Protocol (SNMP) is used to communicate management information between the network management stations and the agents in the network elements.

3.1. Goals of the Architecture

The SNMP explicitly minimizes the number and complexity of management functions realized by the management agent itself. This goal is attractive in at least four respects:

- (1) The development cost for management agent software necessary to support the protocol is accordingly reduced.
- (2) The degree of management function that is remotely supported is accordingly increased, thereby admitting fullest use of internet resources in the management task.
- (3) The degree of management function that is remotely supported is accordingly increased, thereby imposing the fewest possible restrictions on the form and sophistication of management tools.
- (4) Simplified sets of management functions are easily understood and used by developers of network management tools.

A second goal of the protocol is that the functional paradigm for monitoring and control be sufficiently extensible to accommodate additional, possibly unanticipated aspects of network operation and management.

A third goal is that the architecture be, as much as possible, independent of the architecture and mechanisms of particular hosts or particular gateways.

3.2. Elements of the Architecture

The SNMP architecture articulates a solution to the network management problem in terms of:

Case, Fedor, Schoffstall, & Davin

[Page 4]

□

RFC 1067

SNMP

August 1988

- (1) the scope of the management information communicated by the protocol,
- (2) the representation of the management information communicated by the protocol,
- (3) operations on management information supported by the protocol,
- (4) the form and meaning of exchanges among management entities,

- (5) the definition of administrative relationships among management entities, and
- (6) the form and meaning of references to management information.

3.2.1. Scope of Management Information

The scope of the management information communicated by operation of the SNMP is exactly that represented by instances of all non-aggregate object types either defined in Internet-standard MIB or defined elsewhere according to the conventions set forth in Internet-standard SMI [2].

Support for aggregate object types in the MIB is neither required for conformance with the SMI nor realized by the SNMP.

3.2.2. Representation of Management Information

Management information communicated by operation of the SNMP is represented according to the subset of the ASN.1 language [6] that is specified for the definition of non-aggregate types in the SMI.

The SGMP adopted the convention of using a well-defined subset of the ASN.1 language [6]. The SNMP continues and extends this tradition by utilizing a moderately more complex subset of ASN.1 for describing managed objects and for describing the protocol data units used for managing those objects. In addition, the desire to ease eventual transition to OSI-based network management protocols led to the definition in the ASN.1 language of an Internet-standard Structure of Management Information (SMI) [2] and Management Information Base (MIB) [3]. The use of the ASN.1 language, was, in part, encouraged by the successful use of ASN.1 in earlier efforts, in particular, the SGMP. The restrictions on the use of ASN.1 that are part of the SMI contribute to the simplicity espoused and validated by experience with the SGMP.

Case, Fedor, Schoffstall, & Davin

[Page 5]

□

RFC 1067

SNMP

August 1988

Also for the sake of simplicity, the SNMP uses only a subset of the basic encoding rules of ASN.1 [7]. Namely, all encodings use the definite-length form. Further, whenever permissible, non-constructor encodings are used rather than constructor encodings. This restriction applies to all aspects of ASN.1 encoding, both for the top-level protocol data units and the data objects they contain.

3.2.3. Operations Supported on Management Information

The SNMP models all management agent functions as alterations or inspections of variables. Thus, a protocol entity on a logically remote host (possibly the network element itself) interacts with the management agent resident on the network element in order to retrieve (get) or alter (set) variables. This strategy has at least two positive consequences:

- (1) It has the effect of limiting the number of essential management functions realized by the management agent to two: one operation to assign a value to a specified configuration or other parameter and another to retrieve such a value.
- (2) A second effect of this decision is to avoid introducing into the protocol definition support for imperative management commands: the number of such commands is in practice ever-increasing, and the semantics of such commands are in general arbitrarily complex.

The strategy implicit in the SNMP is that the monitoring of network state at any significant level of detail is accomplished primarily by polling for appropriate information on the part of the monitoring center(s). A limited number of unsolicited messages (traps) guide the timing and focus of the polling. Limiting the number of unsolicited messages is consistent with the goal of simplicity and minimizing the amount of traffic generated by the network management function.

The exclusion of imperative commands from the set of explicitly supported management functions is unlikely to preclude any desirable management agent operation. Currently, most commands are requests either to set the value of some parameter or to retrieve such a value, and the function of the few imperative commands currently supported is easily accommodated in an asynchronous mode by this management model. In this scheme, an imperative command might be realized as the setting of a parameter value that subsequently triggers the desired action. For example, rather than implementing a "reboot command," this action might be invoked by simply setting a parameter indicating the number of seconds until system reboot.

Case, Fedor, Schoffstall, & Davin

[Page 6]

□

RFC 1067

SNMP

August 1988

3.2.4. Form and Meaning of Protocol Exchanges

The communication of management information among management entities is realized in the SNMP through the exchange of protocol messages. The form and meaning of those messages is defined below in Section 4.

Consistent with the goal of minimizing complexity of the management agent, the exchange of SNMP messages requires only an unreliable datagram service, and every message is entirely and independently represented by a single transport datagram. While this document specifies the exchange of messages via the UDP protocol [8], the mechanisms of the SNMP are generally suitable for use with a wide variety of transport services.

3.2.5. Definition of Administrative Relationships

The SNMP architecture admits a variety of administrative relationships among entities that participate in the protocol. The entities residing at management stations and network elements which communicate with one another using the SNMP are termed SNMP

application entities. The peer processes which implement the SNMP, and thus support the SNMP application entities, are termed protocol entities.

A pairing of an SNMP agent with some arbitrary set of SNMP application entities is called an SNMP community. Each SNMP community is named by a string of octets, that is called the community name for said community.

An SNMP message originated by an SNMP application entity that in fact belongs to the SNMP community named by the community component of said message is called an authentic SNMP message. The set of rules by which an SNMP message is identified as an authentic SNMP message for a particular SNMP community is called an authentication scheme. An implementation of a function that identifies authentic SNMP messages according to one or more authentication schemes is called an authentication service.

Clearly, effective management of administrative relationships among SNMP application entities requires authentication services that (by the use of encryption or other techniques) are able to identify authentic SNMP messages with a high degree of certainty. Some SNMP implementations may wish to support only a trivial authentication service that identifies all SNMP messages as authentic SNMP messages.

For any network element, a subset of objects in the MIB that pertain to that element is called a SNMP MIB view. Note that the names of the object types represented in a SNMP MIB view need not belong to a

Case, Fedor, Schoffstall, & Davin

[Page 7]

□

RFC 1067

SNMP

August 1988

single sub-tree of the object type name space.

An element of the set { READ-ONLY, READ-WRITE } is called an SNMP access mode.

A pairing of a SNMP access mode with a SNMP MIB view is called an SNMP community profile. A SNMP community profile represents specified access privileges to variables in a specified MIB view. For every variable in the MIB view in a given SNMP community profile, access to that variable is represented by the profile according to the following conventions:

- (1) if said variable is defined in the MIB with "Access:" of "none," it is unavailable as an operand for any operator;
- (2) if said variable is defined in the MIB with "Access:" of "read-write" or "write-only" and the access mode of the given profile is READ-WRITE, that variable is available as an operand for the get, set, and trap operations;
- (3) otherwise, the variable is available as an operand for the get and trap operations.
- (4) In those cases where a "write-only" variable is an

operand used for the get or trap operations, the value given for the variable is implementation-specific.

A pairing of a SNMP community with a SNMP community profile is called a SNMP access policy. An access policy represents a specified community profile afforded by the SNMP agent of a specified SNMP community to other members of that community. All administrative relationships among SNMP application entities are architecturally defined in terms of SNMP access policies.

For every SNMP access policy, if the network element on which the SNMP agent for the specified SNMP community resides is not that to which the MIB view for the specified profile pertains, then that policy is called a SNMP proxy access policy. The SNMP agent associated with a proxy access policy is called a SNMP proxy agent. While careless definition of proxy access policies can result in management loops, prudent definition of proxy policies is useful in at least two ways:

- (1) It permits the monitoring and control of network elements which are otherwise not addressable using the management protocol and the transport protocol. That is, a proxy agent may provide a protocol conversion function allowing a management station to apply a consistent management

Case, Fedor, Schoffstall, & Davin

[Page 8]

□

RFC 1067

SNMP

August 1988

framework to all network elements, including devices such as modems, multiplexors, and other devices which support different management frameworks.

- (2) It potentially shields network elements from elaborate access control policies. For example, a proxy agent may implement sophisticated access control whereby diverse subsets of variables within the MIB are made accessible to different management stations without increasing the complexity of the network element.

By way of example, Figure 1 illustrates the relationship between management stations, proxy agents, and management agents. In this example, the proxy agent is envisioned to be a normal Internet Network Operations Center (INOC) of some administrative domain which has a standard managerial relationship with a set of management agents.

Domain: the administrative domain of the element
 PCommunity: the name of a community utilizing a proxy agent
 DCommunity: the name of a direct community

Figure 1
 Example Network Management Configuration

Case, Fedor, Schoffstall, & Davin

[Page 10]

□

RFC 1067

SNMP

August 1988

3.2.6. Form and Meaning of References to Managed Objects

The SMI requires that the definition of a conformant management protocol address:

- (1) the resolution of ambiguous MIB references,
- (2) the resolution of MIB references in the presence multiple MIB versions, and
- (3) the identification of particular instances of object types defined in the MIB.

3.2.6.1. Resolution of Ambiguous MIB References

Because the scope of any SNMP operation is conceptually confined to objects relevant to a single network element, and because all SNMP references to MIB objects are (implicitly or explicitly) by unique variable names, there is no possibility that any SNMP reference to any object type defined in the MIB could resolve to multiple instances of that type.

3.2.6.2. Resolution of References across MIB Versions

The object instance referred to by any SNMP operation is exactly that specified as part of the operation request or (in the case of a get-next operation) its immediate successor in the MIB as a whole. In particular, a reference to an object as part of some version of the Internet-standard MIB does not resolve to any object that is not part of said version of the Internet-standard MIB, except in the case that the requested operation is get-next and the specified object name is lexicographically last among the names of all objects presented as part of said version of the Internet-Standard MIB.

3.2.6.3. Identification of Object Instances

The names for all object types in the MIB are defined explicitly either in the Internet-standard MIB or in other documents which conform to the naming conventions of the SMI. The SMI requires that conformant management protocols define mechanisms for identifying individual instances of those object types for a particular network element.

Each instance of any object type defined in the MIB is identified in SNMP operations by a unique name called its "variable name." In general, the name of an SNMP variable is an OBJECT IDENTIFIER of the form *x.y*, where *x* is the name of a non-aggregate object type defined in the MIB and *y* is an OBJECT IDENTIFIER fragment that, in a way

Case, Fedor, Schoffstall, & Davin

[Page 11]

□

RFC 1067

SNMP

August 1988

specific to the named object type, identifies the desired instance.

This naming strategy admits the fullest exploitation of the semantics of the GetNextRequest-PDU (see Section 4), because it assigns names for related variables so as to be contiguous in the lexicographical ordering of all variable names known in the MIB.

The type-specific naming of object instances is defined below for a number of classes of object types. Instances of an object type to which none of the following naming conventions are applicable are named by OBJECT IDENTIFIERS of the form *x.0*, where *x* is the name of said object type in the MIB definition.

For example, suppose one wanted to identify an instance of the variable *sysDescr*. The object class for *sysDescr* is:

```
iso org dod internet mgmt mib system sysDescr
 1   3   6   1   2   1   1   1
```

Hence, the object type, *x*, would be 1.3.6.1.2.1.1.1 to which is appended an instance sub-identifier of 0. That is, 1.3.6.1.2.1.1.1.0 identifies the one and only instance of *sysDescr*.

3.2.6.3.1. ifTable Object Type Names

The name of a subnet interface, *s*, is the OBJECT IDENTIFIER value of the form *i*, where *i* has the value of that instance of the *ifIndex* object type associated with *s*.

For each object type, *t*, for which the defined name, *n*, has a prefix of *ifEntry*, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.s*, where *s* is the name of the subnet interface about which *i* represents information.

For example, suppose one wanted to identify the instance of the variable *ifType* associated with interface 2. Accordingly, *ifType.2* would identify the desired instance.

3.2.6.3.2. atTable Object Type Names

The name of an AT-cached network address, *x*, is an OBJECT IDENTIFIER of the form *l.a.b.c.d*, where *a.b.c.d* is the value (in the familiar "dot" notation) of the *atNetAddress* object type associated with *x*.

The name of an address translation equivalence *e* is an OBJECT IDENTIFIER value of the form *s.w*, such that *s* is the value of that instance of the *atIndex* object type associated with *e* and such that *w* is the name of the AT-cached network address associated with *e*.

Case, Fedor, Schoffstall, & Davin

[Page 12]

□

RFC 1067

SNMP

August 1988

For each object type, *t*, for which the defined name, *n*, has a prefix of *atEntry*, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.y*, where *y* is the name of the address translation equivalence about which *i* represents information.

For example, suppose one wanted to find the physical address of an entry in the address translation table (ARP cache) associated with an IP address of 89.1.1.42 and interface 3. Accordingly, *atPhysAddress.3.1.89.1.1.42* would identify the desired instance.

3.2.6.3.3. *ipAddrTable* Object Type Names

The name of an IP-addressable network element, *x*, is the OBJECT IDENTIFIER of the form *a.b.c.d* such that *a.b.c.d* is the value (in the familiar "dot" notation) of that instance of the *ipAdEntAddr* object type associated with *x*.

For each object type, *t*, for which the defined name, *n*, has a prefix of *ipAddrEntry*, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.y*, where *y* is the name of the IP-addressable network element about which *i* represents information.

For example, suppose one wanted to find the network mask of an entry in the IP interface table associated with an IP address of 89.1.1.42. Accordingly, *ipAdEntNetMask.89.1.1.42* would identify the desired instance.

3.2.6.3.4. *ipRoutingTable* Object Type Names

The name of an IP route, *x*, is the OBJECT IDENTIFIER of the form *a.b.c.d* such that *a.b.c.d* is the value (in the familiar "dot" notation) of that instance of the *ipRouteDest* object type associated with *x*.

For each object type, *t*, for which the defined name, *n*, has a prefix of *ipRoutingEntry*, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.y*, where *y* is the name of the IP route about which *i* represents information.

For example, suppose one wanted to find the next hop of an entry in the IP routing table associated with the destination of 89.1.1.42. Accordingly, *ipRouteNextHop.89.1.1.42* would identify the desired instance.

3.2.6.3.5. tcpConnTable Object Type Names

The name of a TCP connection, *x*, is the OBJECT IDENTIFIER of the form a.b.c.d.e.f.g.h.i.j such that a.b.c.d is the value (in the familiar

Case, Fedor, Schoffstall, & Davin

[Page 13]

□

RFC 1067

SNMP

August 1988

"dot" notation) of that instance of the tcpConnLocalAddress object type associated with *x* and such that f.g.h.i is the value (in the familiar "dot" notation) of that instance of the tcpConnRemoteAddress object type associated with *x* and such that e is the value of that instance of the tcpConnLocalPort object type associated with *x* and such that j is the value of that instance of the tcpConnRemotePort object type associated with *x*.

For each object type, *t*, for which the defined name, *n*, has a prefix of tcpConnEntry, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.y*, where *y* is the name of the TCP connection about which *i* represents information.

For example, suppose one wanted to find the state of a TCP connection between the local address of 89.1.1.42 on TCP port 21 and the remote address of 10.0.0.51 on TCP port 2059. Accordingly, tcpConnState.89.1.1.42.21.10.0.0.51.2059 would identify the desired instance.

3.2.6.3.6. egpNeighTable Object Type Names

The name of an EGP neighbor, *x*, is the OBJECT IDENTIFIER of the form a.b.c.d such that a.b.c.d is the value (in the familiar "dot" notation) of that instance of the egpNeighAddr object type associated with *x*.

For each object type, *t*, for which the defined name, *n*, has a prefix of egpNeighEntry, an instance, *i*, of *t* is named by an OBJECT IDENTIFIER of the form *n.y*, where *y* is the name of the EGP neighbor about which *i* represents information.

For example, suppose one wanted to find the neighbor state for the IP address of 89.1.1.42. Accordingly, egpNeighState.89.1.1.42 would identify the desired instance.

4. Protocol Specification

The network management protocol is an application protocol by which the variables of an agent's MIB may be inspected or altered.

Communication among protocol entities is accomplished by the exchange of messages, each of which is entirely and independently represented within a single UDP datagram using the basic encoding rules of ASN.1 (as discussed in Section 3.2.2). A message consists of a version identifier, an SNMP community name, and a protocol data unit (PDU). A protocol entity receives messages at UDP port 161 on the host with which it is associated for all messages except for those which report traps (i.e., all messages except those which contain the Trap-PDU). Messages which report traps should be received on UDP port 162 for further processing. An implementation of this protocol need not accept messages whose length exceeds 484 octets. However, it is recommended that implementations support larger datagrams whenever feasible.

It is mandatory that all implementations of the SNMP support the five PDUs: GetRequest-PDU, GetNextRequest-PDU, GetResponse-PDU, SetRequest-PDU, and Trap-PDU.

```
RFC1067-SNMP DEFINITIONS ::= BEGIN
```

```
IMPORTS
```

```
    ObjectName, ObjectSyntax, NetworkAddress, IpAddress, TimeTicks
    FROM RFC1065-SMI;
```

```
-- top-level message
```

```
Message ::=
    SEQUENCE {
        version          -- version-1 for this RFC
        INTEGER {
            version-1(0)
        },
        community        -- community name
        OCTET STRING,
        data              -- e.g., PDUs if trivial
        ANY              -- authentication is being used
    }
```

```

-- protocol data units

    PDUs ::=
        CHOICE {
            get-request
                GetRequest-PDU,

            get-next-request
                GetNextRequest-PDU,

            get-response
                GetResponse-PDU,

            set-request
                SetRequest-PDU,

            trap
                Trap-PDU
        }

-- the individual PDUs and commonly used
-- data types will be defined later

END

```

4.1. Elements of Procedure

This section describes the actions of a protocol entity implementing the SNMP. Note, however, that it is not intended to constrain the internal architecture of any conformant implementation.

In the text that follows, the term transport address is used. In the case of the UDP, a transport address consists of an IP address along with a UDP port. Other transport services may be used to support the SNMP. In these cases, the definition of a transport address should be made accordingly.

The top-level actions of a protocol entity which generates a message are as follows:

- (1) It first constructs the appropriate PDU, e.g., the GetRequest-PDU, as an ASN.1 object.
- (2) It then passes this ASN.1 object along with a community name its source transport address and the destination transport address, to the service which implements the desired authentication scheme. This authentication

service returns another ASN.1 object.

- (3) The protocol entity then constructs an ASN.1 Message object, using the community name and the resulting ASN.1 object.
- (4) This new ASN.1 object is then serialized, using the basic encoding rules of ASN.1, and then sent using a transport service to the peer protocol entity.

Similarly, the top-level actions of a protocol entity which receives a message are as follows:

- (1) It performs a rudimentary parse of the incoming datagram to build an ASN.1 object corresponding to an ASN.1 Message object. If the parse fails, it discards the datagram and performs no further actions.
- (2) It then verifies the version number of the SNMP message. If there is a mismatch, it discards the datagram and performs no further actions.
- (3) The protocol entity then passes the community name and user data found in the ASN.1 Message object, along with the datagram's source and destination transport addresses to the service which implements the desired authentication scheme. This entity returns another ASN.1 object, or signals an authentication failure. In the latter case, the protocol entity notes this failure, (possibly) generates a trap, and discards the datagram and performs no further actions.
- (4) The protocol entity then performs a rudimentary parse on the ASN.1 object returned from the authentication service to build an ASN.1 object corresponding to an ASN.1 PDU object. If the parse fails, it discards the datagram and performs no further actions. Otherwise, using the named SNMP community, the appropriate profile is selected, and the PDU is processed accordingly. If, as a result of this processing, a message is returned then the source transport address that the response message is sent from shall be identical to the destination transport address that the original request message was sent to.

4.1.1.1. Common Constructs

Before introducing the six PDU types of the protocol, it is appropriate to consider some of the ASN.1 constructs used frequently:

```

-- request/response information

RequestID ::=
    INTEGER

ErrorStatus ::=
    INTEGER {
        noError(0),
        tooBig(1),
        noSuchName(2),
        badValue(3),
        readOnly(4)
        genErr(5)
    }

ErrorIndex ::=
    INTEGER

-- variable bindings

VarBind ::=
    SEQUENCE {
        name
            ObjectName,

        value
            ObjectSyntax
    }

VarBindList ::=
    SEQUENCE OF
        VarBind

```

RequestIDs are used to distinguish among outstanding requests. By use of the RequestID, an SNMP application entity can correlate incoming responses with outstanding requests. In cases where an unreliable datagram service is being used, the RequestID also provides a simple means of identifying messages duplicated by the network.

A non-zero instance of ErrorStatus is used to indicate that an

exception occurred while processing a request. In these cases, ErrorIndex may provide additional information by indicating which variable in a list caused the exception.

The term variable refers to an instance of a managed object. A variable binding, or VarBind, refers to the pairing of the name of a variable to the variable's value. A VarBindList is a simple list of variable names and corresponding values. Some PDUs are concerned

only with the name of a variable and not its value (e.g., the GetRequest-PDU). In this case, the value portion of the binding is ignored by the protocol entity. However, the value portion must still have valid ASN.1 syntax and encoding. It is recommended that the ASN.1 value NULL be used for the value portion of such bindings.

4.1.2. The GetRequest-PDU

The form of the GetRequest-PDU is:

```

GetRequest-PDU ::=
  [0]
    IMPLICIT SEQUENCE {
      request-id
        RequestID,

      error-status      -- always 0
        ErrorStatus,

      error-index      -- always 0
        ErrorIndex,

      variable-bindings
        VarBindList
    }

```

The GetRequest-PDU is generated by a protocol entity only at the request of its SNMP application entity.

Upon receipt of the GetRequest-PDU, the receiving protocol entity responds according to any applicable rule in the list below:

- (1) If, for any object named in the variable-bindings field, the object's name does not exactly match the name of some object available for get operations in the relevant MIB view, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is noSuchName, and the value of the error-index field is the index of said object name component in the received

Case, Fedor, Schoffstall, & Davin

[Page 19]

□

RFC 1067

SNMP

August 1988

message.

- (2) If, for any object named in the variable-bindings field, the object is an aggregate type (as defined in the SMI), then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is noSuchName, and the value of the error-index field is the index of said object name component in the received message.
- (3) If the size of the GetResponse-PDU generated as described

below would exceed a local limitation, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is tooBig, and the value of the error-index field is zero.

- (4) If, for any object named in the variable-bindings field, the value of the object cannot be retrieved for reasons not covered by any of the foregoing rules, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is genErr and the value of the error-index field is the index of said object name component in the received message.

If none of the foregoing rules apply, then the receiving protocol entity sends to the originator of the received message the GetResponse-PDU such that, for each object named in the variable-bindings field of the received message, the corresponding component of the GetResponse-PDU represents the name and value of that variable. The value of the error-status field of the GetResponse-PDU is noError and the value of the error-index field is zero. The value of the request-id field of the GetResponse-PDU is that of the received message.

4.1.3. The GetNextRequest-PDU

The form of the GetNextRequest-PDU is identical to that of the GetRequest-PDU except for the indication of the PDU type. In the ASN.1 language:

```
GetNextRequest-PDU ::=
    [1]
        IMPLICIT SEQUENCE {
            request-id
                RequestID,
```

Case, Fedor, Schoffstall, & Davin

[Page 20]

□

RFC 1067

SNMP

August 1988

```

        error-status          -- always 0
            ErrorStatus,

        error-index          -- always 0
            ErrorIndex,

        variable-bindings
            VarBindList
    }
```

The GetNextRequest-PDU is generated by a protocol entity only at the request of its SNMP application entity.

Upon receipt of the GetNextRequest-PDU, the receiving protocol entity responds according to any applicable rule in the list below:

- (1) If, for any object name in the variable-bindings field, that name does not lexicographically precede the name of some object available for get operations in the relevant MIB view, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is noSuchName, and the value of the error-index field is the index of said object name component in the received message.
- (2) If the size of the GetResponse-PDU generated as described below would exceed a local limitation, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is tooBig, and the value of the error-index field is zero.
- (3) If, for any object named in the variable-bindings field, the value of the lexicographical successor to the named object cannot be retrieved for reasons not covered by any of the foregoing rules, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is genErr and the value of the error-index field is the index of said object name component in the received message.

If none of the foregoing rules apply, then the receiving protocol entity sends to the originator of the received message the GetResponse-PDU such that, for each name in the variable-bindings field of the received message, the corresponding component of the

Case, Fedor, Schoffstall, & Davin

[Page 21]

□

RFC 1067

SNMP

August 1988

GetResponse-PDU represents the name and value of that object whose name is, in the lexicographical ordering of the names of all objects available for get operations in the relevant MIB view, together with the value of the name field of the given component, the immediate successor to that value. The value of the error-status field of the GetResponse-PDU is noError and the value of the errorindex field is zero. The value of the request-id field of the GetResponse-PDU is that of the received message.

4.1.3.1. Example of Table Traversal

One important use of the GetNextRequest-PDU is the traversal of conceptual tables of information within the MIB. The semantics of this type of SNMP message, together with the protocol-specific mechanisms for identifying individual instances of object types in the MIB, affords access to related objects in the MIB as if they enjoyed a tabular organization.

By the SNMP exchange sketched below, an SNMP application entity might extract the destination address and next hop gateway for each entry

in the routing table of a particular network element. Suppose that this routing table has three entries:

Destination	NextHop	Metric
10.0.0.99	89.1.1.42	5
9.1.2.3	99.0.0.3	3
10.0.0.51	89.1.1.42	5

The management station sends to the SNMP agent a GetNextRequest-PDU containing the indicated OBJECT IDENTIFIER values as the requested variable names:

```
GetNextRequest ( ipRouteDest, ipRouteNextHop, ipRouteMetric1 )
```

The SNMP agent responds with a GetResponse-PDU:

```
GetResponse (( ipRouteDest.9.1.2.3 = "9.1.2.3" ),
              ( ipRouteNextHop.9.1.2.3 = "99.0.0.3" ),
              ( ipRouteMetric1.9.1.2.3 = 3 ))
```

The management station continues with:

```
GetNextRequest ( ipRouteDest.9.1.2.3,
                 ipRouteNextHop.9.1.2.3,
```

Case, Fedor, Schoffstall, & Davin

[Page 22]

□

RFC 1067

SNMP

August 1988

```
ipRouteMetric1.9.1.2.3 )
```

The SNMP agent responds:

```
GetResponse (( ipRouteDest.10.0.0.51 = "10.0.0.51" ),
              ( ipRouteNextHop.10.0.0.51 = "89.1.1.42" ),
              ( ipRouteMetric1.10.0.0.51 = 5 ))
```

The management station continues with:

```
GetNextRequest ( ipRouteDest.10.0.0.51,
                 ipRouteNextHop.10.0.0.51,
                 ipRouteMetric1.10.0.0.51 )
```

The SNMP agent responds:

```
GetResponse (( ipRouteDest.10.0.0.99 = "10.0.0.99" ),
              ( ipRouteNextHop.10.0.0.99 = "89.1.1.42" ),
              ( ipRouteMetric1.10.0.0.99 = 5 ))
```

The management station continues with:

```
GetNextRequest ( ipRouteDest.10.0.0.99,
                 ipRouteNextHop.10.0.0.99,
                 ipRouteMetric1.10.0.0.99 )
```

As there are no further entries in the table, the SNMP agent returns those objects that are next in the lexicographical ordering of the known object names. This response signals the end of the routing table to the management station.

4.1.4. The GetResponse-PDU

The form of the GetResponse-PDU is identical to that of the GetRequest-PDU except for the indication of the PDU type. In the ASN.1 language:

```
GetResponse-PDU ::=
  [2]
    IMPLICIT SEQUENCE {
      request-id
      RequestID,
```

Case, Fedor, Schoffstall, & Davin

[Page 23]

□

RFC 1067

SNMP

August 1988

```
error-status
  ErrorStatus,
```

```
error-index
  ErrorIndex,
```

```
variable-bindings
  VarBindList
```

```
}
```

The GetResponse-PDU is generated by a protocol entity only upon receipt of the GetRequest-PDU, GetNextRequest-PDU, or SetRequest-PDU, as described elsewhere in this document.

Upon receipt of the GetResponse-PDU, the receiving protocol entity presents its contents to its SNMP application entity.

4.1.5. The SetRequest-PDU

The form of the SetRequest-PDU is identical to that of the GetRequest-PDU except for the indication of the PDU type. In the ASN.1 language:

```
SetRequest-PDU ::=
  [3]
    IMPLICIT SEQUENCE {
      request-id
```

```

        RequestID,

        error-status      -- always 0
        ErrorStatus,

        error-index       -- always 0
        ErrorIndex,

        variable-bindings
        VarBindList
    }

```

The SetRequest-PDU is generated by a protocol entity only at the request of its SNMP application entity.

Upon receipt of the SetRequest-PDU, the receiving entity responds according to any applicable rule in the list below:

- (1) If, for any object named in the variable-bindings field,

Case, Fedor, Schoffstall, & Davin

[Page 24]

□

RFC 1067

SNMP

August 1988

the object is not available for set operations in the relevant MIB view, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is noSuchName, and the value of the error-index field is the index of said object name component in the received message.

- (2) If, for any object named in the variable-bindings field, the contents of the value field does not, according to the ASN.1 language, manifest a type, length, and value that is consistent with that required for the variable, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is badValue, and the value of the error-index field is the index of said object name in the received message.
- (3) If the size of the Get Response type message generated as described below would exceed a local limitation, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is tooBig, and the value of the error-index field is zero.
- (4) If, for any object named in the variable-bindings field, the value of the named object cannot be altered for reasons not covered by any of the foregoing rules, then the receiving entity sends to the originator of the received message the GetResponse-PDU of identical form, except that the value of the error-status field is genErr and the value of the error-index field is the index of

said object name component in the received message.

If none of the foregoing rules apply, then for each object named in the variable-bindings field of the received message, the corresponding value is assigned to the variable. Each variable assignment specified by the SetRequest-PDU should be effected as if simultaneously set with respect to all other assignments specified in the same message.

The receiving entity then sends to the originator of the received message the GetResponse-PDU of identical form except that the value of the error-status field of the generated message is noError and the value of the error-index field is zero.

Case, Fedor, Schoffstall, & Davin

[Page 25]

□

RFC 1067

SNMP

August 1988

4.1.6. The Trap-PDU

The form of the Trap-PDU is:

```
Trap-PDU ::=
    [4]
```

```
IMPLICIT SEQUENCE {
    enterprise          -- type of object generating
                       -- trap, see sysObjectID in [2]
    OBJECT IDENTIFIER,

    agent-addr         -- address of object generating
    NetworkAddress, -- trap

    generic-trap       -- generic trap type
    INTEGER {
        coldStart(0),
        warmStart(1),
        linkDown(2),
        linkUp(3),
        authenticationFailure(4),
        egpNeighborLoss(5),
        enterpriseSpecific(6)
    },

    specific-trap      -- specific code, present even
    INTEGER,           -- if generic-trap is not
                       -- enterpriseSpecific

    time-stamp         -- time elapsed between the last
    TimeTicks,         -- (re)initialization of the network
                       -- entity and the generation of the
                       trap

    variable-bindings  -- "interesting" information
```

```

        VarBindList
    }

```

The Trap-PDU is generated by a protocol entity only at the request of the SNMP application entity. The means by which an SNMP application entity selects the destination addresses of the SNMP application entities is implementation-specific.

Upon receipt of the Trap-PDU, the receiving protocol entity presents its contents to its SNMP application entity.

Case, Fedor, Schoffstall, & Davin

[Page 26]

□

RFC 1067

SNMP

August 1988

The significance of the variable-bindings component of the Trap-PDU is implementation-specific.

Interpretations of the value of the generic-trap field are:

4.1.6.1. The coldStart Trap

A coldStart(0) trap signifies that the sending protocol entity is reinitializing itself such that the agent's configuration or the protocol entity implementation may be altered.

4.1.6.2. The warmStart Trap

A warmStart(1) trap signifies that the sending protocol entity is reinitializing itself such that neither the agent configuration nor the protocol entity implementation is altered.

4.1.6.3. The linkDown Trap

A linkDown(2) trap signifies that the sending protocol entity recognizes a failure in one of the communication links represented in the agent's configuration.

The Trap-PDU of type linkDown contains as the first element of its variable-bindings, the name and value of the ifIndex instance for the affected interface.

4.1.6.4. The linkUp Trap

A linkUp(3) trap signifies that the sending protocol entity recognizes that one of the communication links represented in the agent's configuration has come up.

The Trap-PDU of type linkUp contains as the first element of its variable-bindings, the name and value of the ifIndex instance for the affected interface.

4.1.6.5. The authenticationFailure Trap

An authenticationFailure(4) trap signifies that the sending protocol

entity is the addressee of a protocol message that is not properly authenticated. While implementations of the SNMP must be capable of generating this trap, they must also be capable of suppressing the emission of such traps via an implementation-specific mechanism.

4.1.6.6. The `egpNeighborLoss` Trap

An `egpNeighborLoss(5)` trap signifies that an EGP neighbor for whom

Case, Fedor, Schoffstall, & Davin

[Page 27]

□

RFC 1067

SNMP

August 1988

the sending protocol entity was an EGP peer has been marked down and the peer relationship no longer obtains.

The Trap-PDU of type `egpNeighborLoss` contains as the first element of its variable-bindings, the name and value of the `egpNeighAddr` instance for the affected neighbor.

4.1.6.7. The `enterpriseSpecific` Trap

A `enterpriseSpecific(6)` trap signifies that the sending protocol entity recognizes that some enterprise-specific event has occurred. The `specific-trap` field identifies the particular trap which occurred.

Case, Fedor, Schoffstall, & Davin

[Page 28]

□

RFC 1067

SNMP

August 1988

5. Definitions

RFC1067-SNMP DEFINITIONS ::= BEGIN

IMPORTS

```

    ObjectName, ObjectSyntax, NetworkAddress, IpAddress, TimeTicks
    FROM RFC1065-SMI;

```

```

-- top-level message

```

```

Message ::=

```

```

    SEQUENCE {
        version          -- version-1 for this RFC
            INTEGER {
                version-1(0)
            },

        community        -- community name
            OCTET STRING,

        data              -- e.g., PDUs if trivial
            ANY           -- authentication is being used
    }

```

```

-- protocol data units

```

```

PDUs ::=

```

```

    CHOICE {

        get-request
            GetRequest-PDU,

        get-next-request
            GetNextRequest-PDU,

        get-response
            GetResponse-PDU,

        set-request
            SetRequest-PDU,

        trap
            Trap-PDU
    }

```

```

-- PDUs

GetRequest-PDU ::=
    [0]
        IMPLICIT PDU

GetNextRequest-PDU ::=
    [1]
        IMPLICIT PDU

GetResponse-PDU ::=
    [2]
        IMPLICIT PDU

SetRequest-PDU ::=
    [3]
        IMPLICIT PDU

PDU ::=
    SEQUENCE {
        request-id
            INTEGER,

        error-status      -- sometimes ignored
            INTEGER {
                noError(0),
                tooBig(1),
                noSuchName(2),
                badValue(3),
                readOnly(4),
                genErr(5)
            },

        error-index      -- sometimes ignored
            INTEGER,

        variable-bindings -- values are sometimes ignored
            VarBindList
    }

Trap-PDU ::=
    [4]
        IMPLICIT SEQUENCE {
            enterprise      -- type of object generating
                           -- trap, see sysObjectID in [2]

            OBJECT IDENTIFIER,

```

□
RFC 1067

SNMP

August 1988

```

agent-addr      -- address of object generating
                 NetworkAddress, -- trap

generic-trap    -- generic trap type
  INTEGER {
    coldStart(0),
    warmStart(1),
    linkDown(2),
    linkUp(3),
    authenticationFailure(4),
    eggNeighborLoss(5),
    enterpriseSpecific(6)
  },

specific-trap   -- specific code, present even
  INTEGER,      -- if generic-trap is not
                -- enterpriseSpecific

time-stamp      -- time elapsed between the last
                 TimeTicks, -- (re)initialization of the
                 network
                 -- entity and the generation of the
                 trap

variable-bindings -- "interesting" information
  VarBindList
}

-- variable bindings

VarBind ::=
  SEQUENCE {
    name
      ObjectName,

    value
      ObjectSyntax
  }

VarBindList ::=
  SEQUENCE OF
  VarBind

END

```

Case, Fedor, Schoffstall, & Davin
□
RFC 1067

SNMP

[Page 31]
August 1988

6. Acknowledgements

This memo was influenced by the IETF SNMP Extensions working group:

Karl Auerbach, Epilogue Technology
K. Ramesh Babu, Excelan
Amatzia Ben-Artzi, 3Com/Bridge
Lawrence Besaw, Hewlett-Packard
Jeffrey D. Case, University of Tennessee at Knoxville
Anthony Chung, Sytek
James Davidson, The Wollongong Group
James R. Davin, Proteon
Mark S. Fedor, NYSERNet
Phill Gross, The MITRE Corporation
Satish Joshi, ACC
Dan Lynch, Advanced Computing Environments
Keith McCloghrie, The Wollongong Group
Marshall T. Rose, The Wollongong Group (chair)
Greg Satz, cisco
Martin Lee Schoffstall, Rensselaer Polytechnic Institute
Wengyik Yeong, NYSERNet

Case, Fedor, Schoffstall, & Davin

[Page 32]

□

RFC 1067

SNMP

August 1988

7. References

- [1] Cerf, V., "IAB Recommendations for the Development of Internet Network Management Standards", RFC 1052, IAB,

April 1988.

- [2] Rose, M., and K. McCloghrie, "Structure and Identification of Management Information for TCP/IP-based internets", RFC 1065, TWG, August 1988.
- [3] McCloghrie, K., and M. Rose, "Management Information Base for Network Management of TCP/IP-based internets", RFC 1066, TWG, August 1988.
- [4] Case, J., M. Fedor, M. Schoffstall, and J. Davin, "A Simple Network Management Protocol", Internet Engineering Task Force working note, Network Information Center, SRI International, Menlo Park, California, March 1988.
- [5] Davin, J., J. Case, M. Fedor, and M. Schoffstall, "A Simple Gateway Monitoring Protocol", RFC 1028, Proteon, University of Tennessee at Knoxville, Cornell University, and Rensselaer Polytechnic Institute, November 1987.
- [6] Information processing systems - Open Systems Interconnection, "Specification of Abstract Syntax Notation One (ASN.1)", International Organization for Standardization, International Standard 8824, December 1987.
- [7] Information processing systems - Open Systems Interconnection, "Specification of Basic Encoding Rules for Abstract Notation One (ASN.1)", International Organization for Standardization, International Standard 8825, December 1987.
- [8] Postel, J., "User Datagram Protocol", RFC 768, USC/Information Sciences Institute, November 1980.

Case, Fedor, Schoffstall, & Davin

□

[Page 33]