TECHNICAL PERFORMANCE RECORD Radar Tower Display System (RTDS)										
FACILITY					DATES		SUPERVISOR'S			
			(ATCT, TRACON, ETC	C.)		FROM:	TO:	SIGNATURE		
LOCATION						EQUIPMENT RTDS		FREQ.		
		(CITY, STATE, AIRPORT, C	OTHER)	Ī		T		Т	
DATE	UTC	MTI OSS (dB)	NORMAL OSS (dB)	Broadband Beacon OSS (dB)	Normal Video Amplitude (v)	MTI Video Amplitude (v)	Composite Video Input Amplitude (P-P)	Remarks	INITIALS	
NOMINAL				Ш	2	2	0			
MINIMUM										
MAXIMUM										

TECHN	ICAL PEI	RFORMAN	ICE REC	ORD			Radar Tower Display System (RTDS)							
FACILITY										SUPERVISOR'S				
(ATCT, TRACON, ETC.)									•	SIGNATURE				
LOCATION								EQUIPMENT RTDS					FREQ.	
(CITY, STATE, AIRPORT, OTHER)													Remarks	1
DATE	UTC	Beacon Video Amplitude (v)	Beacon Video Pulse Width (µs)	Analog Map Video (v)	Spare Video Amplitude (v)	Spare Video Pulse Width (µs)	Radar Pretrigger Amplitude (v)	Radar Pretrigger Pulse Width (µs)	ACP Amplitude (v)	ACP Pulse Width (µs)	ARP Amplitude (v)	ARP Pulse Width (µs)	Tremune	Initials
NOMINAL														
MINIMUM														
MAXIMUM														