

RNP AR

Approach Parameter Chart

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Column Explanation | This column provides the name of the parameter to be compared, e.g., threshold crossing height, vertical angle, waypoint location. | This column explains the purpose of the parameter, (e.g., anchor the vertical path, anchor the lateral path), constraint the location of the path, etc. | This column provides the significance of the parameter to the actual operation of the aircraft on the procedure if it were to be incorrect or out of tolerance | This column provides the largest cycle to cycle change in the parameter that may safely be accepted without concern when validating the procedure. The numerical tolerances are all plus or minus values. | This column provides the parameter that would require issuance of a procedure amendment under rules of 8260.19D. For non-numeric parameters, no change is allowed. Blank if the parameter does not appear in 8260.19D | |
| General | Airport Name | Location | Similar named procedures at other airports | Exact match | Yes | |
| General | Procedure ID | Access to correct procedure in flight | Wrong routing if incorrect | Exact match | Yes | Naming: the translation of the packed data after unpacking means the same thing as the 8260 procedure name, procedure ID from 8260.19D. We are only considering RNP AR |
| Routes & Missed Approach | Transition | Adds ways to access the procedure | Wrong routing if incorrect | Exact match | Yes (Based on change {read "add"} to | |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|--------------------------|--------------------|------------------------------------------------------------------------------------|-----------------------------------------------------|-------------|---------------------------------------------------------------|---------|
| Routes & Missed Approach | Path Terminators | Define the lateral path between waypoints | Changes could relocate the path between terminators | Exact match | Yes (Based on the fact that this would change the course.) | |
| Routes & Missed Approach | Magnetic Course | Define the lateral path when certain path terminators are used, e.g., Cx, Vx, etc. | Changes could relocate the path between terminators | 1 degree | | |
| Routes & Missed Approach | Recommended NAVAID | Determines conversion of magnetic to true course for certain legs types, e.g., Cx | Erroneous ground track | Exact match | | |
| Routes & Missed Approach | Waypoint Name | Anchor the lateral path | Wrong routing if incorrect | Exact match | Yes | |
| Routes & Missed Approach | Waypoint Sequence | Orders the lateral path | Wrong routing if incorrect | Exact match | Yes (Based on the fact that this would change the course.) | |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|--------------------------|---------------------------|------------------------------------------------------------------------------------|-----------------------------------------------------------|-------------|------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Routes & Missed Approach | Turn Direction | In some cases affects the path, for instance a DF to a point 180 out from the path | Differences could affect obstacle clearance | Exact match | Yes (Based on the fact that this would change the course.) | Applies particularly to fly-by and fly-over transitions between leg types. Application to RF leg type is implementation dependent since RF turns are over specified (direction, center, end points and radius) and all four are not necessary to define the turn although they must be consistent. |
| Routes & Missed Approach | Turn Radius | Exact placement of the lateral path through a turn | Differences could affect obstacle clearance or separation | 0.01 NM | | Applies only to RF |
| Routes & Missed Approach | Turn Center Location | Exact placement of the lateral path through a turn | Depending on systems, this may affect turn location | 60 feet | | Applies only to RF. See NOTE in waypoint location comments. |
| Routes & Missed Approach | Turn Start / End Location | Exact placement of the lateral path through a turn | Depending on systems, this may affect turn location | 60 feet | | Applies only to RF. See NOTE in waypoint location comments. |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|--------------------------|-------------------------------|---------------------------------------------------|-----------------------------------------------------------|-------------|-------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Routes & Missed Approach | Fly-over / Fly-by designation | Air traffic constraints or obstacle constraints | Differences could affect obstacle clearance or separation | | Fly-over / Fly-by designation | Air traffic constraints or obstacle constraints |
| Routes & Missed Approach | RNP value | Performance required, alert threshold for cockpit | Improper alerting for crew, OEA potential violation | Exact match | Yes (Based on a change to minimums) | This parameter is an example of one where a comparison failure can be mitigated operationally and the procedure does not have to be invalidated for the database cycle. |
| Routes & Missed Approach | Altitude Constraint Type | Vertical path construction limits | AT, AT Above, AT Below, Window | Exact match | Yes (Considered a change to the altitude) | |
| Routes & Missed Approach | Altitude Constraint Values | Vertical path construction limits | Changes could result in loss of separation | 10 feet | Yes (Considered a change to the altitude) | |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|--------------------------|------------------------|------------------------------------------|------------------------------------------------------|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Routes & Missed Approach | Path Angles | Anchors vertical path to waypoint or LTP | Safety of flight / obstacle clearance | 0.01 degree | Yes, because it is tied to changes of either the TCH or the altitude at the PFAF | Path Angles |
| Routes & Missed Approach | Speed Constraint Type | Controls the meaning of the constraint | May define the exact speed, or a limit, or a minimum | Exact match | Yes, where charted | CAUTION: The three types are only available in one current generation FMS. Speed constraints are treated as "AT or BELOW" by the others. Some systems do not handle speed constraints automatically. Note: See Maximum Airspeeds throughout the Radius to a Fix Leg Segment below. |
| Routes & Missed Approach | Speed Constraint Value | Path following in turns, airspace | Changes could result in loss of separation | 1 knot | This is another example of a parameter that if incorrect, could be mitigated by crew action and the procedure still utilized and corrected later. Crew can enter speed constraints through the MCDU. | No verification of speed data exists |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|------------|------------------------------------------|--------------------------------------------------|--------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Point Data | Waypoint name | Define the lateral (and sometimes vertical) path | Changes could drastically move / change the path | Exact match | Yes | |
| Point Data | Waypoint location (latitude & longitude) | Geographically anchor the path | Differences could affect obstacle clearance | 60 feet | Yes, if a change to the chart is necessary or a change is necessary for the FAS Data Block of an LPV procedure. | <p>The distance measure for all "location" type data refers to the radial distance between the airborne data location and the source data location. An acceptable method of calculation is provided for reference with this matrix, although others are possible.</p> <p>Note: It would also be acceptable to determine the 60 foot equivalent in delta latitude/longitude at the equator and apply the difference test using that threshold to the latitude and longitude of the two locations; this difference to be less than 0.4 arc seconds in either (or both) directions.</p> |

| Section | Compared Parameter | Procedure Use | Significance | Tolerance | Amendment Required in 8260.19D | Comment |
|-------------|----------------------------|-----------------------------------------------------|------------------------------------------------|-------------|--------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Runway Data | Runway Threshold Location | Anchors lateral and vertical path on final approach | Safety of flight | 25 feet | Yes | See Note in waypoint location comments. Latitude / longitude difference to be less than 0.18 arc seconds |
| Runway Data | Runway Threshold Elevation | Anchors lateral and vertical path on final approach | Differences affect vertical obstacle clearance | 1 foot | Yes | |
| Runway Data | Threshold crossing height | Anchors lateral and vertical path on final approach | Differences affect vertical obstacle clearance | 1 foot | Yes | |
| Runway Data | Runway Name (18L, 34R) | Chart cross check | Serves same purpose as a waypoint name | Exact match | Yes | |

Maximum Airspeeds throughout the Radius to a Fix Leg Segment

(Indicated airspeed in knots by Aircraft Category)

| Flight Segment | CAT A | CAT B | CAT C | CAT D | CAT E |
|----------------------------------------------------------|--------------|--------------|--------------|--------------|-----------------|
| Initial & Intermediate (IAF to FAF) | 150 | 150 | 250 | 250 | 250 |
| Final (FAF to DA) | 90 | 120 | 140 | 165 | As Specified |
| Missed Approach (DA to missed approach holding point) | 110 | 150 | 250 | 265 | As Specified |

Note: Do not exceed the maximum airspeeds shown in Table throughout the RF leg segment. A missed approach prior to Decision Altitude (DA) requires maintaining the segment speed to the DA and then observing any speed limitations specified for the missed approach segment.