

Print

Project Name: PIB

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-09 15:20:47.919452

Status: Verified

IFDC 6/0971 PIB IAP HATTIESBURG/LAUREL RGNL, HATTIESBURG-LAUREL, MS. RNAV (GPS) RWY 36, AMDT 1A... LNAV MDA/HAT 700/404, CAT C VISIBILITY 1 1/8. CIRCLING CAT B MDA/HAA 800/502. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HBG ALTIMETER SETTING: INCREASE LPV DA TO 597 FEET; INCREASE LNAV/VNAV DA TO 676 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING HBG ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. CHANGE VISIBILITY REDUTION BY HELICOPTERS NOTE TO READ: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART VDP AT 1.14 NM TO RW36. THIS IS RNAV (GPS) RWY 36, AMDT 1B. 2604091520-PERM

Digitally signed by  
**CASEY D HILL**  
Apr 14, 2026

