

[Print](#)

Project Name: SPI

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-20 15:38:38.982983

Status: Verified

!FDC 6/4922 SPI IAP ABRAHAM LINCOLN CAPITAL, SPRINGFIELD, IL. ILS OR LOC RWY 31, AMDT 2C... S-LOC 31 CAT C VISIBILITY 1 3/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE AAA ALTIMETER SETTING: INCREASE S-ILS 31 DA TO 848 FEET; INCREASE ALL MDAS 60 FEET AND S-LOC 31 VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D/E 1/4 SM. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE S-ILS 31 CAT E VISIBILITY TO 3/4 SM AND S-LOC 31 CATS C/D TO 1 3/4 SM. THIS IS ILS OR LOC RWY 31, AMDT 2D. 2604201538-PERM

Digitally signed by
CASEY D HILL
Apr 24, 2026

