

Print

Project Name: LKR RNAV (GPS) RWY 24

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-30 16:30:31.099196

Status: Verified

IFDC 6/9728 LKR IAP LANCASTER COUNTY-MC WHIRTER FLD, LANCASTER, SC. RNAV (GPS) RWY 24, AMDT 1B... LNAV CAT C VISIBILITY 1 3/8. CHART VDP AT 1.30 NM TO RW24. CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE 3.15/TCH 38.6). CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE UZA ALTIMETER SETTING: INCREASE LPV DA TO 805 FEET; INCREASE LNAV/VNAV DA TO 1086 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING UZA ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. CHANGE WHEN VGSI INOPERATIVE NOTE TO READ: STRAIGHT-IN/CIRCLING RWY 24 AT NIGHT, OPERATIONAL VGSI REQUIRED, REMAIN ON OR ABOVE VGSI GLIDEPATH UNTIL THRESHOLD. THIS IS RNAV (GPS) RWY 24, AMDT 1C. 2603301630-PERM

Digitally signed by
CASEY D HILL
Apr 09, 2026

