

Print

Project Name: IWD

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-24 13:29:53.089222

Status: Verified

IFDC 6/3470 IWD IAP GOGEBIC/IRON COUNTY, IRONWOOD, MI. RNAV (GPS) RWY 27, ORIG-A... LNAV CAT C VISIBILITY 1 1/2. DELETE *LNAV ONLY. CHANGE MIN ALT AT BADVE TO READ: BADVE/2.60 NM TO RW27 2100. CHANGE CHART VDP TO READ: CHART VDP AT 1.90 NM TO RW27. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CATS C/D VISIBILITY TO 1 7/8 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ASX ALTIMETER SETTING: INCREASE LPV DA TO 1562 FEET; INCREASE LNAV/VNAV DA TO 2298 FEET; INCREASE ALL MDAS 140 FEET AND LNAV VISIBILITY CATS C/D 3/8 SM AND CIRCLING VISIBILITY CAT B 1/4 SM. CHANGE NOTE BARO-VNAV AND VDP NA TO READ: BARO-VNAV AND VDP NA WHEN USING ASX ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. DELETE NOTE WHEN USING ASHLAND ALTIMETER SETTING: FOR INOPERATIVE MALSR, INCREASE LNAV CAT B VISIBILITY TO 1 1/4 MILE. DELETE NOTE WHEN USING ASHLAND ALTIMETER SETTING: INOPERATIVE TABLE DOES NOT APPLY TO LNAV/VNAV ALL CATS AND LNAV CAT A. THIS IS RNAV (GPS) RWY 27, ORIG-B. 2603241329-PERM

Digitally signed by
CASEY D HILL
Mar 26, 2026

