

[Print](#)

Project Name: AAF, FL, Update NA at Night-Remove RW14 20:1 Pens, add RW36

Project Reason: RWY 14 20:1 Penetrations no longer exist. Update RWY 14 Night Restrictions on RNAV (GPS) RWY 14 AMDT 2C and RNAV (GPS) RWY 6 AMDT 1C. RWY 14 Night Restrictions were already updated on RNAV (GPS) RWY 24 AMDT 1E and RNAV (GPS) RWY 32 AMDT 2F. RWY18-26 is Unlit. RWY 18 has 20:1 penetrations which drives the Circling NA at Night Restriction. RWY 36 does not have 20:1 penetrations but from an external Inquiry, QC recommended adding Circling NA to RWY 36 to all IAPs to prevent confusion between a note restricting RWY 18 at night but not RWY 36 at night. Updated Arrivals NA at TERES note due to addition of T336 to the fix.

Last Updated By: Michael McCartney

Last Updated At: 2025-02-13 19:42:03.116748

Status: Verified

5/6835

IFDC X/XXXX AAF IAP APALACHICOLA RGNL-CLEVE RANDOLPH FLD, APALACHICOLA, FL. RNAV (GPS) RWY 14, AMDT 2C... PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: STRAIGHT-IN RWY 14 NA AT NIGHT. 20:1 IS CLEAR. CHANGE CIRCLING NA AT NIGHT NOTE TO READ: CIRCLING RWY 6, 18, 24, 32, 36 NA AT NIGHT. CHANGE HELICOPTER NOTE TO READ: RWY 14 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NA. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ECP ALTIMETER SETTING AND INCREASE ALL MDAS 140 FEET AND LNAV VISIBILITY CAT C/D 3/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/2 SM. CHANGE PLANVIEW NOTE TO READ: PROCEDURE NA FOR ARRIVALS AT TERES ON T336 SOUTHEAST BOUND. THIS IS RNAV (GPS) RWY 14, AMDT 2D. 2502131942-PERM

Digitally signed by
ROBERT G HAMILTON
Apr 15, 2025

