

[Print](#)

Project Name: SAR

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-15 18:25:29.687204

Status: Verified

!FDC 6/7344 SAR IAP SPARTA COMMUNITY-HUNTER FLD, SPARTA, IL. RNAV (GPS) RWY 36, ORIG-B... LNAV CAT C VISIBILITY 1 5/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BLV ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING BLV ALTIMETER SETTING. CHANGE CIRCLING NA NOTE TO READ: CIRCLING NA TO RWYS 9 AND 27. CHART NOTE: RWY 36 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 36, ORIG-C. 2604151825-PERM

Digitally signed by

CASEY D HILL

May 04, 2026

