

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
MADEE (RNAV)	SIX	MADEE.MADEE6	FIVE	10/05/2023	

TRANSITION ROUTES:

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	MAA	Crossing Altitudes / Fixes
KONAH	KONAH.MADEE6	KONAH	KONAH						AT/ABOVE 16000
			EVRTT	333.04	06.29	10000	3200		BETWEEN 14000 AND 16000
			MADEE	333.01	19.60	4000	3200		

ARRIVAL ROUTE DESCRIPTION:

LANDING BLI RWY 16: FROM MADEE ON TRACK 332.95/18.20 TO CROSS GERRD BETWEEN 5000 AND 7000, THEN ON TRACK 306.52/11.38 TO CROSS UCAKI AT OR ABOVE 4000, THEN ON TRACK 343.76/6.30 TO CROSS YAANO AT OR ABOVE 2000, THEN ON TRACK 343.76. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.

LANDING BLI RWY 34: FROM MADEE ON TRACK 322.26/14.56 TO CROSS TUBTY AT 4000 AND AT 210 KIAS, THEN ON TRACK 343.85. EXPECT RNAV (RNP/GPS) RWY 34 APPROACH OR RADAR VECTORS TO FINAL APPROACH COURSE.

LANDING CZBB/CYXX: FROM MADEE ON TRACK 332.95/18.20 TO CROSS GERRD BETWEEN 5000 AND 7000, THEN ON TRACK 306.52/11.38 TO CROSS UCAKI AT OR ABOVE 4000, THEN ON TRACK 343.76/6.30 TO CROSS YAANO AT OR ABOVE 2000, THEN ON TRACK 343.76. EXPECT RADAR VECTORS TO FINAL APPROACH COURSE.

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

NOTE: BLI LANDING NORTH EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER TUBTY. NOTE:

BLI LANDING SOUTH EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER YAANO.

NOTE: LANDING CYXX AND CZBB: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER YAANO.

NOTE: LANDING CZBB: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER UCAKI.

FIXES AND/OR HOLDING PATTERNS:

CHART HOLDING AT TECUV: HOLD NW, RT, 135.90 INBOUND, 4 NM LEGS.

COMMUNICATIONS:

CHART: VICTORIA TERMINAL APP CON 132.7

CHART: WHIDBEY APP CON

CHART: BLI TWR

CHART: CYXX TWR

CHART: CRANBROOK RADIO

AIRPORTS SERVED:

AIRPORT ID	CITY	STATE
BLI	BELLINGHAM	WA
CYXX	ABBOTSFORD, BRITISH COLUMBIA	
CZBB	DELTA, BRITISH COLUMBIA	

QUALITY
14
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
MADEE (RNAV)	SIX	MADEE.MADEE6	FIVE	10/05/2023	

LOST COMMUNICATIONS PREFERENCES:

LANDING BLI RWY 16: AFTER UCAKI CONDUCT RNAV (RNP) Z RWY 16 APPROACH; IF UNABLE, PROCEED TO YAANO MAINTAIN 2000 AND PROCEED TO TECUV AND HOLD.
LANDING CYXX AND CZBB: AFTER YAANO MAINTAIN 2000 AND PROCEED TO TECUV AND HOLD.

REMARKS:

COMMS ARE ATC SPECIFIC; CHART AS INDICATED.
MVA AFTER YAANO CONFIRMED AS 2000 FT MSL BY NAV CANADA ATC.
10000 FT MEA KONAH-EVRTT NEEDED FOR D/D/I NAVIGATION.
OBST AAO 2123 MSL LOCATED DOWNSTREAM IN RWY TRANSITIONS (BETWEEN MADEE-GERRD) DRIVES A 3200 FT MOCA VALUE.

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: SAT (RNP 2.0)
MAG VAR: BLI 16E/2020.
CHART AT TUBTY TERMINUS: BLI LDG RWY 34.
CHART AT YAANO TERMINUS: LDG CYXX AND CZBB.
CHART AT YAANO TERMINUS: BLI LDG RWY 16.

FLIGHT INSPECTED BY:

Digitally signed by
MARK J ROGERS
CASEY D HILL

ORGANIZATION:

AJF

DATE:

06/26/2025

Flight Inspected Signature: _____

DEVELOPED BY:

Jul 07, 2025

CASIMIR TABAKA (ROBERT SWINSON) *Digitally signed by*
CASEY D HILL

AJV-A432

3/28/2025

Developed By Signature: _____

APPROVED BY:

Digitally signed by Jul 07, 2025

CASIMIR TABAKA
CASEY D HILL

AJV-A432

Approved By Signature: _____

CHANGES:

1. AMENDED RWY 34 ARRIVAL ROUTE DESCRIPTION; CHANGED CROSSING RESTRICTION AT TUBTY FROM AT/ABOVE 3000 TO AT 4000.
2. REPLACED PAE VOR/DME WITH NEW KONAH WP AS BEGINNING STAR FIX WITH A RESTRICTION OF AT/ABOVE 16000 AND AT/BELOW 270 KIAS.
3. CHANGED RESTRICTION AT EVRTT FROM AT/ABOVE 14000 TO BETWEEN 14000 AND 16000.
4. DELETED PROCEDURAL DATA NOTE: "LANDING BLI RUNWAY 16, CYXX AND CZBB: FOR NON-GPS EQUIPPED AIRCRAFT, CVV DME MUST BE OPERATIONAL."
5. AMENDED COMMUNICATIONS DATA FOR VICTORIA TERMINAL APP CON TO ONLY 132.7.
6. ENROUTE MOCA VALUES CHANGED FROM 2100 TO 3200; MEA AT MADEE FROM 3000 TO 4000.
7. REMOVED K IDENT FOR BLI FROM 17.1 FORM.
8. REMOVED REMARK 3000 MEA EVRTT MADEE NEEDED TO ALLOW DESCENT TO 3000 ON RWY 34 TRSN.
9. ADDED AAO OBST REMARK.
10. ADDED COMM REMARK.
7/8/2025: THIS IS A UPDATED COPY OF THE FORM DEVELOPED ON 03/28/205
CHANGED PROCEDURAL NOTE: LANDING CYXX: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER YAANO TO LANDING CZBB OR CYXX
EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER YAANO.
9/10/2025: THIS IS A UPDATED COPY OF THE FORM DEVELOPED ON 03/28/205
CHANGED PROCEDURAL NOTE: LANDING CYXX: EXPECT RADAR VECTORS TO FINAL APPROACH COURSE AFTER YAANO TO LANDING CYXX AND CZBB: EXPECT RADAR VECTORS
TO FINAL APPROACH COURSE AFTER YAANO.

QUALITY
14
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
MADEE (RNAV)	SIX	MADEE.MADEE6	FIVE	10/05/2023	

REASONS:


- 1-3: ATC REQUEST.
4. CVV NO LONGER A CRITICAL DME. UPDATED DME/DME/IRU ANALYSIS.
5. CORRECTION TO THE CURRENT CHARTING AS PREVIOUS 120.7 IS NOT A VICTORIA ATC FREQUENCY.
- 6, 9. OBST LOCATED DOWNSTREAM IN TRANSITION ROUTES; PROTECT FOR ROC VALUE.
7. IAW CURRENT DOCUMENTATION STANDARDS.
8. NO LONGER APPLICABLE.
10. COMMS ARE NON-STANDARD FOR THIS LOCATION.



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STANDARD TERMINAL ARRIVAL (STAR)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

Arrival Name	Number	STAR Computer Code	Superseded Number	Dated	Effective Date
MADEE (RNAV)	SIX	MADEE.MADEE6	FIVE	10/05/2023	
Graphic Depiction 1					



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
STAR (DATA RECORD)**

Arrival Name MADEE (RNAV)		Number SIX		STAR Computer Code MADEE.MADEE6		Superseded Number FIVE		Dated 10/05/2023	Effective Date
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
En Route Transition									
KONAH	475517.88N / 1221641.95W	Y		IF			AT/ABOVE 16000	AT/BELOW 270K	KONAH.MADEE6
EVRTT	480128.26N / 1221828.91W	Y	FB	TF	349.04	06.29	14000B16000		
MADEE	482041.70N / 1222404.81W	Y	FB	TF	349.01	19.60			
Common Route									
MADEE	482041.70N / 1222404.81W	Y		IF					MADEE.MADEE6
GERRD	483832.56N / 1222920.45W	Y	FB	TF	348.95	18.20	5000B7000		
UCAKI	484733.45N / 1223948.81W	Y	FB	TF	322.52	11.38	AT/ABOVE 4000		
YAANO	485351.15N / 1223951.22W	Y	FO	TF	359.76	06.30	AT/ABOVE 2000		
CYXX,CZBB				FM	359.76				
Runway Transition									
MADEE	482041.70N / 1222404.81W	Y		IF					
GERRD	483832.56N / 1222920.45W	Y	FB	TF	348.95	18.20	5000B7000		
UCAKI	484733.45N / 1223948.81W	Y	FB	TF	322.52	11.38	AT/ABOVE 4000		
YAANO	485351.15N / 1223951.22W	Y	FO	TF	359.76	06.30	AT/ABOVE 2000		
KBLI:RWY 16				FM	359.76				
Runway Transition									
MADEE	482041.70N / 1222404.81W	Y		IF					
TUBTY	483412.18N / 1223211.90W	Y	FO	TF	338.26	14.56	AT 4000	AT 210K	
KBLI:RWY 34				FM	359.85				

