

Print

Project Name: 5H4

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Steve Nelson

Last Updated At: 2026-02-18 21:03:52.080067

Status: Verified 6 / 6 8 8 2

!FDC X/XXXX 5H4 IAP HARVEY MUNI, HARVEY, ND. RNAV (GPS) RWY 29, ORIG-E... LNAV/VNAV DA 2100/HAT 493, VISIBILITY CATS A/B/C 1 3/8. LNAV CAT C VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DVL ALTIMETER SETTING: INCREASE LNAV/VNAV DA TO 2230 FEET AND ALL VISIBILITIES 3/8 SM; INCREASE ALL MDAS 140 FEET AND LNAV VISIBILITY CAT C 3/8 SM AND CIRCLING VISIBILITY CAT C 1/2 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV NA WHEN USING DVL ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 29, ORIG-F. 2602182103-PERM

Digitally signed by
CASEY D HILL
Feb 19, 2026

