

[Print](#)

Project Name: ICR

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-23 12:44:09.369173

Status: Verified

IFDC 6/3150 ICR IAP WINNER RGNL, WINNER, SD. RNAV (GPS) RWY 13, ORIG-C... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.35 NM TO RW13. CHANGE MIN ALT AT SKAMP TO READ: SKAMP/2.40 NM TO RW13 2800. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VTN ALTIMETER SETTING: INCREASE LPV DA TO 2451 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 2637 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 200 FEET AND LNAV VISIBILITY CAT C 1/2 SM AND CIRCLING VISIBILITY CATS B/C 3/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING VTN ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -19C OR ABOVE 54C. DELETE VGSI AND RNAV GLIDEPATH NOT COINCIDENT NOTE. THIS IS RNAV (GPS) RWY 13, ORIG-D. 2603231244-PERM

Digitally signed by

CASEY D HILL

Mar 25, 2026

