

Print

Project Name: LBX

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-27 17:29:41.181952

Status: Verified

!FDC 6/6473 LBX IAP TEXAS GULF COAST RGNL, ANGLETON/LAKE JACKSON, TX. RNAV (GPS) RWY 35, AMDT 2B... LNAV CAT C VISIBILITY 1 1/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.11 NM TO RW35. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOU ALTIMETER SETTING: INCREASE LPV DA TO 356 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 509 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CAT D 1/4 SM. CHANGE BARO-VNAV AND VDP NA WHEN USING NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING HOU ALTIMETER SETTING. CHANGE BARO-VNAV NA BELOW NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 35, AMDT 2C. 2603271729-PERM

Digitally signed by
CASEY D HILL
Apr 02, 2026

