

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
POTTER	ONE		NONE		10/19/2010

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 7L/R: CLIMB HEADING 074.00 TO 600, THEN CLIMBING RIGHT TURN ON HEADING 199.00. THENCE...

...EXPECT RADAR VECTORS TO ASSIGNED ROUTE OR DEPICTED FIX. MAINTAIN 4000. EXPECT FURTHER CLEARANCE TO FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: RADAR REQUIRED.

NOTE: MAXIMUM PROCEDURE AIRSPEED LIMITED TO 200 KIAS.

TAKEOFF MINIMUMS:

RWY 7L, 300 - 1 1/8 OR STANDARD WITH MINIMUM CLIMB OF 255 FT PER NM TO 400.

RWY 7R, 300 - 1 OR STANDARD WITH MINIMUM CLIMB OF 285 FT PER NM TO 400.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

RWY 7L: 257 FT MSL POLE 611023.01N/1495506.97W

RWY 7R: 255 FT MSL TREE 610949.20N/1495652.24W

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

CHART: TOP ALTITUDE: 4000

REFERENCE MAG VAR: PANC - 16E EPOCH YR: 2020

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
TED STEVENS ANCHORAGE INTL (PANC)	ANCHORAGE	AK



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
POTTER	ONE		NONE		10/10/19

COMMUNICATIONS:

ATIS, CLNC DEL, GND CON, ANC ATCT, ANC DEP CON

FIXES AND/OR NAVAIDS:

SQA VOR/DME, JOH VOR/DME, TED VOR/DME, ILI NDB/DME, ENA VOR/DME, HOM VOR/DME, MDO VOR/DME.

REMARKS:

FLIGHT INSPECTED BY:

PENDING

Digitally signed by

DAVID DANNER

Aug 12, 2019

OFFICE SYMBOL:

DATE:

DEVELOPED BY:

DAVID DANNER (LORRI DOWNEY)

Digitally signed by

DAVID DANNER

Aug 12, 2019

OFFICE SYMBOL:

AJV-A421

DATE:

06/03/2019

APPROVED BY:

MARLON ROBINSON

Digitally signed by

DAVID DANNER

Aug 12, 2019

OFFICE SYMBOL:

AJV-A420

DATE:

REQUIRED EFFECTIVE DATE:

10/10/2019

COORDINATED WITH:

A4A

ALPA

AOPA

APA

HAI

NBAA



OTHER:

ATA, ZAN, ANC ATCT, AMGR, ANC APP CON, ALASKA DOT, WESTERN FPT

CHANGES - REASONS:

QUALITY
3
CHECKED