

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SEEMS	ONE	SEEMS1.SEEMS	NONE		

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 30: CLIMB ON HEADING 301.93 TO 566, THEN CLIMBING LEFT TURN DIRECT SEEMS, CONTINUE CLIMB IN SEEMS HOLDING PATTERN TO AT/ABOVE 3500 BEFORE PROCEEDING ON COURSE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	---------------------------------	------------------------	----------------------	---------------	-----------------	------------	-------------	--------------------------------

PROCEDURAL DATA NOTES:

PBN REQUIREMENTS NOTES:

RNAV 1 - GPS.

EQUIPMENT REQUIREMENT NOTES:

TAKEOFF MINIMUMS:

RWY 30: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 566.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 30: TREES BEGINNING 1248 FT FROM DER, 83 FT LEFT OF CENTERLINE, UP TO 160 FT MSL. TREE 1263 FT FROM DER, 628 FT RIGHT OF CENTERLINE, 156 FT MSL. TREES AND POLES BEGINNING 1490 FT FROM DER, 102 FT RIGHT OF CENTERLINE, UP TO 160 FT MSL. TREES BEGINNING 1921 FT FROM DER, 161 FT LEFT OF CENTERLINE, UP TO 172 FT MSL. TREES BEGINNING 2234 FT FROM DER, 23 FT LEFT OF CENTERLINE, UP TO 192 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: 2146 FT MSL AAO 373139.00N/1222536.00W

MSA:

MSA FROM KHAF 4500

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: NOT CONDUCTED
CHART HOLDING PATTERN AT SEEMS: HOLD NW, RT, 144.00 INBOUND, 9 NM LEG.
CHART: V27
AIRPORT MV: HAF 15E/1995



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SEEMS	ONE	SEEMS1.SEEMS	NONE		

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
KHAF	HALF MOON BAY	CA

COMMUNICATIONS:

FIXES AND/OR NAVAIDS:

REMARKS:

VEGETATION HEIGHT 100 FT PER FPT.

FLIGHT INSPECTED BY *Digitally signed by*
 BRANDON C EASTIN ***ERIC N SUSKI***
 Feb 06, 2023

OFFICE **DATE**
 FPO 01/26/2023

DEVELOPED BY *Digitally signed by*
 KELLY DEAN ***KELLY D DEAN***
 Nov 30, 2022

OFFICE **DATE**
 AJV-A437 11/17/2022

APPROVED BY *Digitally signed by*
 ERIC SUSKI ***ERIC N SUSKI***
 Feb 06, 2023

OFFICE **DATE** **TITLE**
 AJV-A431 MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A **ALPA** **AOPA** **APA** **HAI** **NBAA** **OTHER:** ZOA, ARPT MGR, NORCAL APP CON

CHANGES - REASONS:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
SEEMS	ONE	SEEMS1.SEEMS	NONE		

<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RWY30 (AER)*	373035.82N/1222949.46W*	N	-	-	-				*DISPL THLD (762 FT)
566 MSL	-	-	-	VA	316.93	-	AT/ABOVE 566		CG 500 FT PER NM TO 566
SEEMS	373533.77N/1223925.74W	Y	FO	DF	-	-			LEFT TURN
SEEMS	373533.77N/1223925.74W	Y	FO	HM	159.00	9.00	AT/ABOVE 3500		RIGHT TURN

