

[Print](#)

Project Name: OCF

Project Reason: Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-08 20:17:02.708848

Status: Verified

IFDC 6/0968 OCF IAP OCALA INTL-JIM TAYLOR FLD, OCALA, FL. RNAV (GPS) RWY 36, AMDT 1A... LNAV CAT C VISIBILITY 7/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.31 NM TO RW36. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GNV ALTIMETER SETTING: INCREASE LPV DA TO 361 FEET; INCREASE LNAV/VNAV DA TO 644 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/2 SM. CHANGE VDP AND BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING GNV ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. CHANGE INOPERATIVE TABLE DOES NOT APPLY TO LPV NOTE TO READ: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, LNAV CATS A/B TO 1 SM, AND LNAV CAT D TO 1 3/8 SM. DELETE FOR INOPERATIVE MALSR WHEN USING GAINSVILLE ALTIMETER SETTING NOTE.. THIS IS RNAV (GPS) RWY 36, AMDT 1B. 2604082017-PERM

Digitally signed by

CASEY D HILL

Apr 14, 2026

