

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
FAIRR	ONE	FAIRR1.FAIRR	NONE		

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

VFR SEGMENT: VFR CLIMB TO ZUTEG, CROSS ZUTEG AT OR ABOVE 1600 ON TRACK 108.61.

IFR SEGMENT: FROM ZUTEG CLIMB ON TRACK 108.61 TO CROSS FAIRR AT OR ABOVE 4700.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PBN REQUIREMENT NOTES:

RNP 0.3 - GPS. AP.

EQUIPMENT REQUIREMENT NOTES:

PROCEDURAL DATA NOTES:

NOTE: USE 59B ALTIMETER SETTING; WHEN NOT RECEIVED, USE 8B0 ALTIMETER SETTING AND CROSS ZUTEG AT OR ABOVE 1800.

NOTE: PILOT MUST ENSURE CDI SENSITIVITY IS SET TO 0.30 NM. CDI MAY BE RESET TO 1.00 NM AFTER FAIRR AS APPLICABLE.

NOTE: USE OF THIS PROCEDURE REQUIRES SPECIFIC AUTHORIZATION BY FAA FLIGHT STANDARDS.

TAKEOFF MINIMUMS:

TAKEOFF OBSTACLES NOTES:

CONTROLLING OBSTACLES:

IDF ALTITUDE CONTROLLING OBSTACLE: 1344 FT MSL, TREE, 453703.00N/0701339.00W.

MSA:

MSA FROM ZUTEG, 5200 WITHIN A 25 NM RADIUS

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

AIRPORT MV: 59B 16W/2020.

CHART: TOP ALTITUDE: ASSIGNED BY ATC.

DME/DME ASSESSMENT: NOT CONDUCTED.

QUALITY
21
CHECKED

AIRPORTS SERVED:

AIRPORT ID	CITY	STATE
59B	JACKMAN	ME

COMMUNICATIONS:

CHART: BOSTON CENTER (ZBW).

FIXES AND/OR NAVAIDS:

REMARKS:

EXISTING AFS-DIRECTED MEMO:
- FAA ORDER 8260.58C, INSTRUMENT PROCEDURE DESIGN INITIAL DEPARTURE FIX CRITERIA.
DEPARTURE CONNECTS TO AIRWAY ZK423 AT FAIRR.
RASS PRESSURE PATTERNS THE SAME.
59B 1178, 8B0 1809.
DIST 8B0 TO ZUTEG: 42.61 NM.
RA = 186.4.
59B IS ON WMSCR.
8B0 IS ON WMSCR.

FLIGHT INSPECTED BY

TERRY HESTER

SIGNATURE

Digitally signed by

RAKE MCGRAW

May 14, 2025

OFFICE

AJF

DATE

04/23/2025

DEVELOPED BY

RICHARD BRUCE

SIGNATURE

Digitally signed by

RICHARD A BRUCE

Nov 14, 2024

OFFICE

AJV-A422

DATE

11/14/2024

APPROVED BY

BEV L. BORDY

SIGNATURE

Digitally signed by

RAKE MCGRAW

May 14, 2025

OFFICE

AJV-A420

DATE

TITLE

MANAGER

REQUIRED EFFECTIVE DATE

COORDINATED WITH:

A4A ☐ ALPA ☐ AOPA ☐ APA ☐ HAI ☒ NBAA ☐ OTHER: ZBW, AMGR

CHANGES - REASONS:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>							<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
FAIRR							ONE	FAIRR1.FAIRR	NONE		
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>		
RW01H	453757.91N/0701455.65W	N	-	-	-	-			VFR SEGMENT		
1600 MSL	-		-	-	-	-					
ZUTEG	453756.09N/0701400.05W	Y	FB	IF	-	-	AT/ABOVE 1600		IFR SEGMENT		
FAIRR	453734.67N/0700307.36W	Y	FB	TF	092.61	7.64	AT/ABOVE 4700				

QUALITY
21
CHECKED