

[Print](#)

Project Name: SGF

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-16 12:56:10.08711

Digitally signed by

ROBERT G HAMILTON

Apr 17, 2026

Status: Verified

6/3765

!FDC X/XXXX SGF IAP SPRINGFIELD-BRANSON NTL, SPRINGFIELD, MO. RNAV (GPS) RWY 2, AMDT 2B... LNAV CAT C VISIBILITY RVR 4500. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP NOTE TO READ: CHART VDP AT 1.26 NM TO RW02. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HFJ ALTIMETER SETTING: INCREASE LPV DA TO 1680 FEET; INCREASE LNAV/VNAV DA TO 1844 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CATS C/D TO RVR 6000 AND CIRCLING VISIBILITY CATS C/D 1/2 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING HFJ ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 SM, LNAV CATS A/B TO RVR 5500, AND LNAV CAT D TO 1 3/8 SM. DELETE FOR INOPERATIVE MALSR, WHEN USING MONETT ALTIMETER SETTING NOTE. THIS IS RNAV (GPS) RWY 2, AMDT 2C. 2604161256-PERM

