Flight Procedures Cover Page	Task Action: FLIGHT CHECK	Task Type: Estimated Chart Date: APWS Task ID: Textual DP 02/20/2025 27692D1187B84C15B		APWS Task ID: 27692D1187B84C15B8A3E566131CDA90	APWS Project ID: A62D75FE2781463D806A24049FE8AF06			
Procedure: Enroute: NO			Specialist: Given, Cody		Agreement Number:			
Airport ID: K33			Airport City: SALEM		State: MO			
Facility ID:	Facility Type:	Flight Inspection Remark Type: New FC Slot						

Procedure Comments:

UTILIZED ACTIVE AIRNAV DATA FOR KK33 ODP.

CLEARED FDC NOTAM 3/5346.

CONTACT ERICK SUSKI: AJV-A431, 405-954-7331.



				FIP	C BASIC	FORM	[
PROCEDURE:				AIRPOF	AIRPORT NAME:			AIRPO	AIRPORT ID:		SPECIAL CONTROL NO:			
TAKEOFF MINIMUMS AND OBSTACLE DP AMDT 0A				SALEM	SALEM MEML			KK33		OP-10-213-24				
FAC ID: KK33 CITY: SALEM				•	ST:			ST: MC)	CHART DA	RT DATE: 02/20/2025			
DFL TYPE:	THIRI	D PARTY:	EST. TIME ON SITE: REIMB. NUMBER: PTS TAS					K ID:						
PROC/T		YES	0.4 27692D1187B84C15B8A3E566131CDA90											
PREFLIGHT NOTES														
REVIEWER:								DATE:						
COMMENTS:									CHECK ONE:					
□FLT								☐ FLT (ΓCK REQ			REJ	REJECT	
													YES	NO
									CPV COM	IPLETE	?		X	
PROCEDURE RESULTS														
INSPECTION DA	ATE:	CREV	N #: N #:	INSTRUM	INSTRUMENT PROCEDURE STATUS:				ARINC CODING:					
12/18/2024		VN53	86 N83	X SAT	X SAT ☐ SAT W/CHANGES ☐ UNSAT					SAT SAT/GOLD UNSAT				
FLIGHT INSPECTOR SIGNATURE:				PRINTEI	PRINTED NAME:						NO	TAM I	INITIAT	TED?
nicholas a varner @ 12/18/2024 17:57				VARNER	VARNER, NICHOLAS ALLEN] YES	X	O
FLIGHT INSPEC	CTOR R	EMARKS:												
IN-FLIGHT OBSTACLE REPORT														
OBSTRUCTION	N ID #: COORDINATES OR LOCATION: GNSS ALTITUDE (MSL): BAROMETRIC ALTITUDE (MSL): HEIGHT ABOVE GI					E GRO	UND LI	EVEL:						

TAKE-OFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

SAC CITY, IA

SAC CITY MUNI (SKI) ORIG 10154 (FAA)

> NOTE: Rwy 18, trees beginning 675' from DER, 673' right of centerline, up to 50' AGL/1279' MSL. Rwy 32, vehicles on road beginning 349' from DER, 584' right of centerline, up to 15' AGL/1264' MSL. Rwy 36, vehicles on road beginning 562' from DER, left and right of centerline, up to 15'AGL/1264'MSL

SALEM, MO

SALEM MEMORIAL (K33)

ORIG 11293 (FAA)

TAKE-OFF MINIMUMS: Rwy 17, 400-21/4 or std. w/min. climb of 300'per NM to 1500.

NOTE: Rwy 17, trees beginning 675' from DER, 675' left of centerline, up to 100' AGL/1349' MSL. Tree 911' from DER, 290' right of centerline, 34' AGL/1275' MSL. Powerline beginning 942' from DER, 745' left of centerline, up to 120' AGL/1369' MSL. Rwy 35, tree 770' from DER, 120' right of centerline, 28' AGL/1249' MSL.

SHELDON, IA

SHELDON MUNI (SHL) ORIG 11181 (FAA)

NOTE: Rwy 15, trees beginning 1347' from DER, 360' left of centerline, up to 98' AGL/1497' MSL. Rwy 33, vehicles on road 615' from DER, on centerline, 15' AGL/1436' MSL. Trees beginning 960' from DER. 367' right of centerline, up to 55' AGL/1464' MSL. Antenna on airport beacon, vehicles on road, trains on railroad tracks and tree beginning 31' from DER, 53' left of centerline, up to 62' AGL/1481' MSL.

ST. CHARLES, MO

20 OCT 2011 to 17 NOV 201

ST. CHARLES COUNTY SMARTT (SET) AMDT 2 05300 (FAA)

TAKE-OFF MINIMUMS: Rwy 36, std. with a min. climb of 262' per NM to 1300, OR 900-21/2 for climb in visual

DEPARTURE PROCEDURE: Rwy 36, for climb in visual conditions: cross St. Charles County Smartt airport at or above 1300 before proceeding on course.

NOTE: Rwy 36, tree 2.3 NM from departure end of runway, 3932' right of centerline, 100' AGL/891' MSL.

ST. JOSEPH, MO

ROSECRANS MEMORIAL (STJ)

AMDT 6 05300 (FAA)

TAKE-OFF MINIMUMS: Rwy 31, 400-21/4 or std. with a min. climb of 325' per NM to 1300.

DEPARTURE PROCEDURE: Rwy 13, climb via heading 132° to 2200 before turning left.

NOTE: Rwy 13, tree 3394' from departure end of runway, 655' left of centerline, 100' AGL/919' MSL. Rwy 17, trees $beginning\,2691' from\, departure\, end\, of\, runway, across$ courseline, up to 109' AGL/928' MSL. Rwy 31, trees beginning 1.18 NM from departure end of runway, 986' left of centerline, up to 100' AGL/1139' MSL.

ST. LOUIS, MO

CREVE COEUR (1H0) AMDT 2 07354 (FAA)



TAKE-OFF MINIMUMS: Rwy16, 300-21/4 or std. w/min. climb of 206' per NM to 800, or alternatively, with standard takeoff minimums and a normal 200' per NM climb gradient, takeoff must occur no later than 1300' prior to departure end of runway. Rwy 34, 300-21/4 or std. w/min. climb of 337' per

DEPARTURE PROCEDURE: Rwy 34, climb heading 338° to 1100 before proceeding on course.

NOTE: Rwy 16, vehicle on road, pole and trees beginning 200' from departure end of runway, 219' right of centerline, up to 100' AGL/546' MSL. Trees beginning 100' from departure end of runway, 356' left of centerline, up to 100' AGL/719' MSL. Rwy 34, multiple trees beginning 1847' from departure end of runway, 418' right of centerline up to 100' AGL/749' MSL. Levee and trees beginning 744' from departure end of runway, 275' left of centerline, up to 90' AGL/612'MSL.

LAMBERT-ST. LOUIS INTL (STL) AMDT 2 10266 (FAA)

TAKE-OFF MINIMUMS: Rwy 11, 200-1 or std. w/ min. climb of 407' per NM to 900. Rwy 30L, 200-1 or std. w/min. climb of 241' per NM to 800. Rwy 30R, 200-11/2 or std. w/ min. climb of 322' per NM to 900.

NOTE: Rwy 6, railroad 578' from DER, 620' left of centerline, 23' AGL/557' MSL. Obstruction light on LDA and atenna on building 1038' from DER, 706' right of centerline, 30' AGL/598' MSL. Rwy 11, multiple signs, trees, towers, and buildings beginning 2348' from DER, 205' left of centerline, up to 219' AGL/774' MSL. Multiple signs, trees, towers, and buildings beginning 2363' from DER, 489' right of centerline, up to 114' AGL/ 694' MSL. Rwy 12L, tree 1331' from DER, 667' right of centerline, 75' AGL/654' MSL.

Rwy 12R, traffic signal and sign beginning 1413' from DER, 702' right of centerline, up to 17' AGL/672' MSL. Tree 1930' from DER, 372' left of centerline, 67' AGL/636' MSL. Rwy 30L, multiple trees, poles, and roads beginning 906' from DER, 600' left of centerline, up to 84' AGL/663' MSL. Obstruction light on LOC 614' from DER, on centerline, 9' AGL/558' MSL. Multiple trees, poles, roads, terrain, and buildings beginning 283' from DER, 185' right of centerline, up to 65' AGL/684' MSL. Rwy 30R, obstruction light on GS 1895' from DER, 899' left of centerline, 28' AGL/587' MSL. Multiple obstruction light on buildings, trees, and electrical system beginning 2039' from DER, 387' right of centerline, up to 81' AGL/670' MSL.

SPIRIT OF ST. LOUIS (SUS)

AMDT 1 10266 (FAA)

TAKE-OFF MINIMUMS: Rwy 8R, 200-11/4 or std. w/min. climb of 238' per NM to 700. Rwy 26L, 200-2 or std. w/ min. climb of 231' per NM to 900.

NOTE: Rwy 8L, multiple trees beginning 1245' from DER, 52' left of centerline, up to 74' AGL/533' MSL. Multiple trees and fence beginning 46' from DER, 72' right of centerline, up to 57' AGL/516' MSL.

Rwy 8R, railroad and antenna on building beginning 142' from DER, 18' left of centerline, up to 33' AGL/482' MSL. Rwy 26L, tree 2239' from DER, 509' right of centerline, up to 62' AGL/521' MSL. Rwy 26R, multiple trees beginning 1898' from DER, 18' left of centerline, up to 130' AGL/589' MSL. Multiple trees beginning 32' from DER, 41' right of centerline, up to 142' AGL/601' MSL.











