

Print

Project Name: CDN RNAV (GPS) RWY 6

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-02-25 15:38:22.022089

Status: Verified FDC # 6/8781

IFDC X/XXXX CDN IAP WOODWARD FLD, CAMDEN, SC. RNAV (GPS) RWY 6, ORIG-A... APT ELEV 303. TDZE 303. LPV DA 583. LNAV/VNAV DA 714. LNAV HAT 477. LNAV CAT C VISIBILITY 1 3/8. CIRCLING CATS A/B/C HAA 537 AND CIRCLING CAT D HAA 597. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH – GPS. ALTERNATE MINIMUMS: STANDARD – NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE CAE ALTIMETER SETTING: INCREASE LPV DA TO 673 FEET; INCREASE LNAV/VNAV DA TO 804 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING CAE ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. 34:1 IS CLEAR. DELETE VISIBILITY REDUCTION BY HELICOPTERS NA. CHART VDP AT 1.45 NM TO RW06. CHART NOTE: CIRCLING RWY 14, 32 NA AT NIGHT. THIS IS RNAV (GPS) RWY 6, ORIG-B. 2602251538-PERM

Digitally signed by
BEV L BORDY
Mar 16, 2026

