WAAS CH 86912 W10A	APP CRS 094°	Rwy Ldg 6006 TDZE 631 Apt Elev 649

RNAV (GPS) RWY 10
SOUTHWEST MICHIGAN RGNL (BEH)

RNP APCH - GPS.

T A Rwy 10 helicopter visibility reduction below ¾ SM NA. For uncompensated Baro-VNAV systems, LNAV/VNAV NA below -20°C or above 54°C. Baro-VNAV and VDP NA when using LWA altimeter setting. When local altimeter setting not received, use LWA altimeter setting: increase LPV DA to 917 feet and all visibilities ⅛ SM; increase LNAV/VNAV DA to 1076 feet and all visibilities ¼ SM; increase all MDAs 40 feet and LNAV visibility Cats C and D ¼ SM.

MISSED APPROACH: Climb to 2500 direct GIDPE and hold.

ASOS	SOUTH BEND APP CON★		CLNC DEL	UNICOM
121.55	118.55	257.8	119.7	123.0 (CTAF) L





CATEGORY		A	B	C	D
LPV	DA	881-¾ 250 (300-¾)			
LNAV/VNAV	DA	1040-1⅛ 409 (400-1⅛)			
LNAV MDA		1040-1 409 (400-1)		1040-1⅛ 409 (400-1⅛)	