

[Print](#)

Project Name: AWM - NEW CIRCLING CRITERIA APPLIED

Project Reason: NEW CIRCLING AREA APPLIED. CIRCLING OBSTRUCTIONS: CAT A: 335 TREE (05-063504) 350840.79N/0901256.98W (1B) 335+300=635 ROUNDED TO 640. CAT B: 382 POLE (2020-ASW-7284-OE) 350951.11N/0901236.95W (4D) 382+300+AC50=732 ROUNDED TO 740 CAT C: 442 TOWER (05-001595) 351030.00N/0901130.00W (5D) 442+300+AC50=792 ROUNDED TO 800 CAT D: 558 TOWER (05-000981) 350517.90N/0901134.90W (4D) 558+300+AC50=908 ROUNDED TO 920. RADII: 1.30, 1.81, 2.85, 3.72. PRIMARY ALTIMETER VIS CHECK FOR ALL PROCEDURES AND ILS OR LOC RWY 17 KEHOE FIX MINIMUMS: 1, 1, 1 1/2, 2 1/4. BACKUP ALTIMETER VIS CHECK: 1, 1, 1 3/4, 2 1/2. BACKUP ALTIMETER NOTE TO BE UPDATED FOR RNAV (GPS) RWY 17 AND RNAV (GPS) RWY 35. CAT C/D +1/4 SM. BACKUP NOTE FOR ILS OR LOC RWY 17 PREVIOUSLY MOVED TO BACK OF -9 FORM. ALTERNATE MINIMUMS TO BE UPDATED FOR RNAV (GPS) RWY 17 AND RNAV (GPS) RWY 35. STANDARD EXCEPT CAT D 800-2 1/4. ALTERNATE MINIMUMS NOT ESTABLISHED FOR ILS OR LOC RWY 17 DUE TO PROCEDURE SHOWING ALTERNATE MINIMUMS AS NA. Order 8260.3, chapter 2, New Circling Criteria Applied.

Last Updated By: Brett Cannon

1/3878

Last Updated At: 2021-08-18 12:59:24.864224

Status: Verified

IFDC X/XXXX AWM IAP WEST MEMPHIS MUNI, WEST MEMPHIS, AR. RNAV (GPS) RWY 17, ORIG-A... CIRCLING CAT B MDA 740/HAA 527, CAT C MDA 800/587, CAT D MDA 920/HAA 707. CIRCLING VISIBILITY CAT D 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MEMPHIS INTL ALTIMETER SETTING AND INCREASE LPV DA TO 513 FEET, LNAV/VNAV DA TO 644 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 60 FEET AND INCREASE VISIBILITY LNAV CAT C AND CIRCLING CAT C AND D 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE.. THIS IS RNAV (GPS) RWY 17, ORIG-B. 2108181259-PERM

Digitally signed by
DAVID TEFFETELLER
Aug 23, 2021

QUALITY
45
CHECKED