

Print

Project Name: JHW RNAV (GPS) RWY 7

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-25 17:55:27.972195

Status: Verified

!FDC 6/6467 JHW IAP CHAUTAUQUA COUNTY/JAMESTOWN, JAMESTOWN, NY. RNAV (GPS) RWY 7, AMDT 1C... LNAV CAT C VISIBILTIIY 1 1/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DKK ALTIMETER SETTING AND INCREASE ALL MDAS 200 FEET AND LNAV VISIBILITY CAT C 5/8 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 3/4 SM. DELETE HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHANGE RWY 7 STRAIGHT-IN/CIRCLING AND CIRCLING TO RWY 13/31 NA AT NIGHT TO READ: CIRCLING RWY 13, 31 NA AT NIGHT. CHART VDP AT 1.09 NM TO RW07. 34:1 IS CLEAR. THIS IS RNAV (GPS) RWY 7, AMDT 1D. 2603251755-PERM

Digitally signed by
CASEY D HILL
Apr 02, 2026

