

[Print](#)

Project Name: DKB RNAV (GPS) RWY 2

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-04 15:46:19.907687

Status: Verified 6/8954

!FDC X/XXXX DKB IAP DE KALB TAYLOR MUNI, DE KALB, IL. RNAV (GPS) RWY 2, ORIG-B... LNAV CAT C VISIBILITY 7/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT VIYUD TO READ: VIYUD/2.60 NM TO RW02 1800. CHANGE CHART VDP TO READ: CHART VDP AT 1.23 NM TO RW02. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO 7/8 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ARR ALTIMETER SETTING: INCREASE LPV DA TO 1268 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 1421 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV NA AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING ARR ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. GS ALT AT JINYO 2700. THIS IS RNAV (GPS) RWY 2, ORIG-C. 2603041546-PERM

Digitally signed by

BEV L BORDY

Mar 17, 2026

