FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

DP NAME						<u>NUMBER</u>	DP COMPUTER CODE	SUPERSEDED I	<u>IUMBER</u>	DAT	<u>ED</u>	ACTUAL EFFECTIVE DATE
LAMON			FOUR	LAMON4.LAMON	THREE		02/25/2021		10/02/202			
TYPE: OB	STACLE	COPTER	SID	SPECIAL	RNAV							
	VY 4: CLIME	ON HEADING		*			LAMON, THENCE CT LAMON, THENCE					
CONTINUE	CLIMB IN F	OLD TO CRO	SS LAMON A	AT OR ABOVE 130	000 BEFOR	E PROCEEDIN	G ON COURSE.					
TRANSITION	ROUTES (C	RAPHIC DEP	ICTION ONL	Y):								
TRANSITION	NAME	TRANSIT COMPUTER		<u>FROM</u> FIX/NAVAID	<u>!</u>	FIX/	<u>TO</u> NAVAID	COURSE	DISTANCE	MEA	MOCA	<u>CROSSING</u> <u>ALTITUDE/FIXES</u>
PBN REQUIR		TES:										
RNAV 1 - GPS	S											
EQUIPMENT	REQUIREM	ENT NOTES:										
PROCEDURA	AL DATA NO	DTES:										
	IDARD WIT			FT/NM TO 7400 5 FT/NM TO 7700								
TREE, TERRA AGRICULTUF	4: AGRICUL AIN BEGINN RAL EQUIPN	TURAL EQUIF IING 73 FT FR MENT 186 FT F MENT BEGINN MENT BEGINN MENT BEGINN MENT BEGINN MENT 506 FT F MENT BEGINN	OM DER, 38 FROM DER, 21 IING 218 FT IING 282 FT IING 315 FT IING 481 FT FROM DER, 3 IING 513 FT IING 546 FT IING 645 FT IING 674 FT IING 774 FT FROM DER, 3 IING 887 FT	7 FT RIGHT OF C 286 FT LEFT OF C FROM DER, 116 F FROM DER, 3 FT FROM DER, 4 FT FROM DER, 109 F 572 FT RIGHT OF FROM DER, 4 FT FROM DER, 218 F FROM DER, 218 F FROM DER, 12 F FROM DER, 13 F FROM DER, 13 F	ENTERLIN CENTERLIN T LEFT OF RIGHT OF T RIGHT OF T LEFT OF CENTERL RIGHT OF T LEFT OF T LEFT OF T RIGHT OF T RIGHT OF T RIGHT OF T RIGHT OF	E, UP TO 8 FT IE, 20 FT AGL/6 CENTERLINE, OF CENTERLINE, CENTERLINE, CENTERLINE, CENTERLINE, CENTERLINE, CENTERLINE, CENTERLINE CENTERLINE CENTERLINE CENTERLINE F CENTERLINE OF CENTERLINE CENTERLINE OF CENTERLINE CENTERLINE CENTERLINE CENTERLINE CENTERLINE	, UP TO 20 FT AGL/6275 FT UP TO 17 FT AGL/6279 FT I E, UP TO 17 FT AGL/6280 F UP TO 17 FT AGL/6282 FT I , UP TO 17 FT AGL/6276 FT ./6283 FT MSL. UP TO 17 FT AGL/6284 FT I , UP TO 17 FT AGL/6277 FT UP TO 17 FT AGL/6278 FT I , UP TO 17 FT AGL/6287 FT E, UP TO 17 FT AGL/6288 F 5279 FT MSL. , UP TO 17 FT AGL/6290 FT	MSL. MSL. T MSL. MSL. MSL. MSL. MSL. MSL. MSL. MSL.				WAL/7L

AGRICULTURAL EQUIPMENT BEGINNING 927 FT FROM DER, 56 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6291 FT MSL. AGRICULTURAL EQUIPMENT BEGINNING 1050 FT FROM DER, 164 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6293 FT MSL.

DP NAMENUMBERDP COMPUTER CODESUPERSEDED NUMBERDATEDACTUAL EFFECTIVE DATELAMONFOURLAMON4.LAMONTHREE02/25/202110/02/2025

AGRICULTURAL EQUIPMENT BEGINNING 1186 FT FROM DER, 266 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6294 FT MSL. TERRAIN. TREES BEGINNING 1261 FT FROM DER, 771 FT LEFT OF CENTERLINE, UP TO 6396 FT MSL.

AGRICULTURAL EQUIPMENT BEGINNING 1300 FT FROM DER, 500 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6296 FT MSL.

AGRICULTURAL EQUIPMENT BEGINNING 1406 FT FROM DER, 604 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6297 FT MSL.

AGRICULTURAL EQUIPMENT BEGINNING 1534 FT FROM DER, 722 FT RIGHT OF CENTERLINE, UP TO 17 FT AGL/6298 FT MSL.

AGRICULTURAL EQUIPMENT 1609 FT FROM DER, 908 FT RIGHT OF CENTERLINE, 17 FT AGL/6299 FT MSL.

NOTE: RWY 22: TERRAIN, FENCE BEGINNING 8 FT FROM DER, 290 FT LEFT OF CENTERLINE, UP TO 6169 FT MSL. BUILDING 22 FT FROM DER, 477 FT RIGHT OF CENTERLINE, 10 FT AGL/6175 FT MSL. VEHICLES ON ROAD 511 FT FROM DER, 608 FT LEFT OF CENTERLINE, 6179 FT MSL. LIGHT POLES 644 FT FROM DER, 424 FT RIGHT OF CENTERLINE, 28 FT AGL/6184 FT MSL. BUILDING 816 FT FROM DER, 716 FT RIGHT OF CENTERLINE, 30 FT AGL/6191 FT MSL. TREE 1001 FT FROM DER, 443 FT RIGHT OF CENTERLINE, 46 FT AGL/6196 FT MSL.

CONTROLLING OBSTACLES:

RWY 4: 7057 MSL AAO 434757.00N/1110021.00W RWY 22: 7296 MSL AAO 434245.00N/1111545.00W

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: 13966 FT MSL AAO 434430.00N/1104809.00W

MSA:

MSA FROM KDJI 15000

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT: NOT CONDUCTED

AIRPORT MV: KDIJ 12E/2015

CHART: HOLDING PATTERN AT LAMON, HOLD W, RT, 088.25 INBOUND, 8 NM LEGS.

AIRPORTS SERVED:

AIRPORT ID CITY STATE

DIJ DRIGGS ID

COMMUNICATIONS:

UNICOM (CTAF), SALT LAKE CITY CENTER

FIXES AND/OR NAVAIDS:

REMARKS:

100 FT VEG HEIGHT USED. PER FPT CHECKLIST.



<u>DP NAME</u> LAMON		OUR LAMON4.LAMON	E SUPERSEDED NUMBER THREE	<u>DATED</u> 02/25/2021	ACTUAL EFFECTIVE DATE 10/02/2025
FLIGHT INSPECTED BY	SIGNATURE	Digitally signed by CASIMIR L TABAKA	OFFICE	DATE	
		Jun 12, 2025			
DEVELOPED BY	<u>SIGNATURE</u> Digitally signed by		OFFICE	DATE	
LEO J. PALMER	LEO PALMER		AJV-A421	03/21/2025	
APPROVED BY	Apr 29, 2025 SIGNATURE	Digitally signed by	<u>OFFICE</u>	DATE	TITLE
DAVE DANNER		CASIMIR L TABAKA	AJV-A421	08/27/2025	MANAGER
		Jun 12, 2025			

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

A4A ALPA AOPA AOPA APA HAI NBAA OTHER: ZLC, AMGR, ID AERO

CHANGES - REASONS:

-DP ROUTE DESCRIPTION: TAKEOFF RWY 4 CHANGED FROM "CLIMB ON HEADING 036.19 TO 6731, THEN CLIMBING LEFT TURN DIRECT LAMON, THENCE ..." TO "TAKEOFF RWY 04: CLIMB ON HEADING 036.19 TO 6757, THEN LEFT TURN DIRECT LAMON THENCE ..." - UPDATED TO CURRENT CRITERIA.

- -DP ROUTE DESCRIPTION TAKEOFF RWY 22 CANGED FROM "CLIMB ON HEADING 216.20 TO 6731, THEN CLIMBING RIGHT TURN DIRECT LAMON, THENCE ..." TO "TAKEOFF RWY 22: CLIMB ON HEADING 216.21 TO 6757, THEN RIGHT TURN DIRECT LAMON THENCE ..." UPDATED TO CURRENT CRITERIA.
- -DP ROUTE DESCRPTION COMMON ROUTE PORTION CHANGED FROM "... CONTINUE CLIMB IN LAMON HOLDING PATTERN (HOLD W, RT, 8 MILE LEGS, 088.25 INBOUND) TO CROSS LAMON AT OR ABOVE 13000 BEFORE PROCEEDING ON COURSE.. "TO "...CONTINUE CLIMB IN HOLD TO CROSS LAMON AT OR ABOVE 13000 BEFORE PROCEEDING ON COURSE.." IAW 8260.46J APP E SEC 1 PARA 2 M.
- -PROCEDURAL DATA NOTES: "NOTE: GPS REQUIRED" AND "NOTE: RNAV 1" UPDATED AND MOVED TO PBN REQUIREMENTS NOTES AS "RNAV 1 GPS". IAW 8260.46J APP E SEC 1 PARA E
- -TAKEOFF MINIMUMS: RWY 4 CHANGED FROM "RWY 4: STANDARD WITH A MINIMUM CLIMB OF 245 FT PER NM TO 7700" TO "RWY 4: STANDARD WITH MINIMUM CLIMB OF 340 FT/NM TO 7400". PENDING AIRNAV DATA WITH RUNWAY EXTENSION TO RWY 22 AND THRESHOLD RELOCATION TO RWY 04, AND RE-EVALUATION OF TERRAIN USING MITRE 3DEP, FPT REQUEST.
- -TAKEOFF MINIMUMS: RWY 22 CHANGED FROM "RWY 22: STANDARD WITH A MINIMUM CLIMB OF 253 FT PER NM TO 8800" TO "RWY 22: STANDARD WITH MINIMUM CLIMB OF 215 FT/PER NM TO 7700". PENDING AIRNAV DATA WITH RUNWAY EXTENSION TO RWY 22 AND THRESHOLD RELOCATION TO RWY 04, AND RE-EVALUATION OF TERRAIN USING MITRE 3DEP. FPT REQUEST.
- -TAKEOFF OBSTACLE NOTES: ADDED/UPDATE OBSTACLES THAT ARE HIGHER/CLOSER THAN THOSE PUBLISHED. NEW OIS SURVEY PUBLISHED 02/64/2024
- -CONTROLLING OBSTACLES CHANGED FROM: RWY 4: 7143 FT MSL TREE 434804.41N/1105953.83W. RWY 22: 7310 FT MSL AAO 434244.43N/1111546.11W. OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 4/22 13790 FT MSL AAO 434413.90N/1104816.00W, 11555 FT MSL AAO 435429.70N/1104640.30W, 10552 FT MSL AAO 433158.40N/1105825.10W, 9219 FT MSL AAO 434757.00N/1110021.00W RWY 22: 7293 MSL AAO 434245.00N/1111545.00W. OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: 13966 FT MSL AAO 434430.00N/1104809.00W" RE-EVALUATION OF TERRAIN USING MITRE 3DEP.
- -ADDITIONAL FLIGHT DATA: ADDED "CHART: HOLDING PATTERN AT LAMON, HOLD W, RT, 088.25 INBOUND, 8 NM LEGS,". IAW 8260.46J APP E SEC 1 PARA 2 M.
- -AIRPORTS SERVED: REMOVED AIRPORT NAME COLUMN. IAW 8260.46J APP E SEC 1 PARA 2N
- -REMARKS: ADDED "100 FT VEG HEIGHT USED. PER FPT CHECKLIST." FOR FUTURE PROCEDURE DEVELOPMENT CONSIDERATION.
- -ADDITIONAL FLIGHT DATA "REFERENCE MAG VAR: KDIJ 12E EPOCH YR: 2015" CHANGED TO "AIRPORT MV: KDIJ 12E/2015". IAW MEMO 283 DATED 6/2/222.
- -MSA: ADDED "MSA FROM KDJI 15000". PER CURRENT CRTIERIA.
 06/11/2025: THIS IS AN UPDATED COPY OY THE FORM DEVELOPED ON 03/21/2025.
 ADDED 10/02/2025 T0 ACTUAL EFFECTIVE DATE.



FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)

DP NAME LAMON						NUMBER FOUR	DP COMPUTER CODE LAMON4.LAMON	SUPERSEDED NUMBER THREE	<u>DATED</u> 02/25/2021	ACTUAL EFFECTIVE DATE 10/02/2025
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FE	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS	
RW04 (AER)	434422.51N/1110605.73W	N	-	-	-	-				
6757 MSL	-	-	-	VA	048.19	-	AT/ABOVE 6757		CG 340 FT PER NM 1	O 7400
LAMON	435734.19N/1111457.68W	Υ	FO	DF	-	-			LEFT TURN	
LAMON	435734.19N/1111457.69W	Υ	FO	НМ	100.25	8.00	AT/ABOVE 13000		RIGHT TURN	
RW22 (AER)	434510.55N/1110451.62W	N		-	-	-				
6757 MSL	-		-	VA	228.21	-	AT/ABOVE 6757		CG 215 FT PER NM 1	O 7700
LAMON	435734.19N/1111457.68W	Υ	FO	DF	-	-			RIGHT TURN	
LAMON	435734.19N/1111457.69W	Υ	FO	НМ	100.25	8.00	AT/ABOVE 13000		RIGHT TURN	

