

[Print](#)

Project Name: FFX

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-12 18:54:05.85611

Status: Verified

!FDC 6/9117 FFX IAP FREMONT MUNI, FREMONT, MI. RNAV (GPS) RWY 19, AMDT 1E... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.33 NM TO RW19. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MKG ALTIMETER SETTING: INCREASE LPV DA TO 1139 FEET; INCREASE LNAV/VNAV DA TO 1360 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING MKG ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 19, AMDT 1F. 2603121854-PERM

Digitally signed by

CASEY D HILL

Mar 17, 2026

