

[Print](#)

Project Name: BFR - RNAV (GPS) RWY 31 NEW CONTROLLING OBSTACLE

Project Reason: LP/LNAV FINAL AND CIRCLING CATS A/B NEW CONTROLLING OBSTACLE: 994 TOWER ANTENNA (2023-AGL-21510-OE-PERMANENT) AC 2C 384941.69N/0862505.50W REQUIRES AN MDA/HAT OF 1260/535 AND CMDA/HAA OF 1300/573. 994 TOWER + 250/300 (ROC) = 1244 WHICH ROUNDS TO 1260/1300. UPDATE PBN REQUIREMENTS NOTE, LOCAL ALTIMETER SETTING NOTE, HELICOPTER VISIBILITY NOTE, ALTERNATE MINIMUMS.

Last Updated By: Jacob Clark

Last Updated At: 2025-03-13 15:45:37.113565

Status: Draft
5/4631



!FDC ~~XXXXX~~ BFR IAP VIRGIL I GRISSOM MUNI, BEDFORD, IN. RNAV (GPS) RWY 31, AMDT 1C... DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BMG ALTIMETER SETTING AND INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C/D 1/4 SM, AND LP VISIBILITY CAT C/D 1/4 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM. CHANGE HELICOPTER VISIBILITY NOTE TO READ: RWY 31 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. ALTERNATE MINIMUMS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE FAS OBST: 860 TOWER 384942N/0862506W. CHART FAS OBST: 994 TOWER 384942N/0862506W. LP MDA 1260/HAT 535 ALL CATS, VIS 1 1/2 CAT C/D. LNAV MDA 1260/HAT 535 ALL CATS, VIS 1 1/2 CAT C/D. CIRCLING MDA 1300/HAA 573 CATS A/B. THIS IS RNAV (GPS) RWY 31, AMDT 1D. 2503131545-PERM

Digitally signed by
CASIMIR L TABAKA
Mar 18, 2025