

[Print](#)

Project Name: FOE

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-13 13:11:13.641812

Status: Verified

!FDC 6/9141 FOE IAP TOPEKA RGNL, TOPEKA, KS. RNAV (GPS) RWY 31, ORIG-B... LNAV CAT C VISIBILITY RVR 5000. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.27 NM TO RW31. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO RVR 4500, LNAV/VNAV ALL CATS TO RVR 4500, AND LNAV CATS C/D TO 1 3/8 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOP ALTIMETER SETTING: INCREASE LPV DA TO 1343 FEET; INCREASE LNAV/VNAV DA TO 1402 FEET AND CATS A/B/C VISIBILITY TO RVR 3500; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CATS C/D TO RVR 5500 AND CIRCLING VISIBILITY CAT D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING TOP ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -17C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 31, ORIG-C. 2603131311-PERM

Digitally signed by
CASEY D HILL
Mar 17, 2026

