

Flight Procedures Cover Page	Task Action: FLIGHT CHECK	Task Type: IAP	Estimated Chart Date: 09/03/2026	APWS Task ID: 41CD84471F0E4BC1A11DA0F6220E2518	APWS Project ID: 0DD1BDEC90AD421BBE7634AAB7655435
Procedure: ILS OR LOC RWY 5 AMDT 14		Enroute: NO	Specialist: Given, Cody		Agreement Number:
Airport ID: KISO			Airport City: KINSTON		State: NC
Facility ID: ISO	Facility Type: ILS	Flight Inspection Remark Type: New FC Slot			
Procedure Comments: FULL AMENDMENT COMPLETED UTILIZING ACTIVE AIRNAV DATA FOR KISO. CLEARED FDC NOTAM 6/4933. CONTACT: RAKE MCGRAW: AJV-A422, 405-954-8711. QUALITY 38 CHECKED QUALITY 39 CHECKED					

LOC/DME I-ISO
111.3
Chan **50**

APP CRS
050°

Rwy Ldg **10960**
TDZE **93**
Apt Elev **93**

ILS or LOC RWY 5

KINSTON RGNL JETPORT AT STALLINGS FLD (ISO)

RADAR required for procedure entry. DME required.

VDP NA when using GSB altimeter setting. When local altimeter setting not received, use GSB altimeter setting and increase S-ILS 5 DA to 336 feet; increase all MDAs 60 feet and S-LOC 5 visibility Cat C/D/E to RVR 4500 and Circling visibility Cat E ¼ SM. For inop ALS, increase S-ILS 5 Cat E visibility to RVR 4000 and S-LOC 05 Cat E visibility RVR 6000. For inop ALS when using GSB altimeter setting, increase S-ILS 5 Cat E visibility to RVR 4000 and increase S-LOC 5 Cat E visibility to 1½ SM.

MALSR

MISSED APPROACH: Climb to 600 then climbing right turn to 2500 on heading 110° and on EWN VOR/DME R-313 to WILUN/EWN 20.9 DME and hold.

AWOS-3
132.75

SEYMOUR JOHNSON APP CON ★
127.3 273.6

KINSTON TOWER ★
120.6 (CTAF) 0 335.55

GND CON
121.9

UNICOM
122.95

Diagram illustrating the ILS for RWY 5. Key features include:

- LOCALIZER 111.3** (I-ISO Chan 50) and **GLIDESLOPE 050°** (H-ISO Chan 83).
- WILUN EWN 20.9** (DME R-313) and **WILUN EWN 113.6** (DME R-313).
- MSA ISO 25 NM** (3100).
- Hold** at 4500/2100.
- Radar Stations:** ZATVA (I-ISO 4.3), ZOMAV (I-ISO 8.1), UHIRO (I-ISO 12.9).
- Altitudes:** 227 ±, 391, 2100, 4500, 2100.
- Angles:** 230°, 050°, 230°.

One Minute Holding Pattern

UHIRO I-ISO 12.9 RADAR

ZOMAV I-ISO 8.1 RADAR

ZATVA I-ISO 4.3

H-ISO 3

H-ISO 2

600

2500

EWN R-313

WILUN

4500

2100

GS 3.00°

TCH 59

4.8 NM

3.8 NM

1.3 NM

1 NM

CATEGORY	A	B	C	D	E
S-ILS 5	293/24 200 (200-½)				
S-LOC 5	480/24	387 (400-½)	480/35 387 (400-¾)		
CIRCLING	540-1 447 (500-1)	560-1 467 (500-1)	700-1¾ 607 (700-1¾)	700-2 607 (700-2)	780-2½ 687 (700-2½)

REIL Rwy 23 0
HIRL Rwy 5-23 0

KINSTON, NORTH CAROLINA

Amtd 13 22JAN26

KINSTON RGNL JETPORT AT STALLINGS FLD (ISO)

35°20'N-77°37'W

ILS or LOC RWY 5