

[Print](#)

Project Name: BMG circling radii increase

Project Reason: Order 8260.3, chapter 2, new circling criteria applied. Only circling minimums verified. Backup altimeter and alternate minimums note updated as required. Controlling obstacles: CAT A 1069 (2C) TREE 390958.69N/0863736.05W, 1069+300=1369 (1380). CAT B/C 1096 (1C) TREE (18-021837) 391047.82N/0863628.31W, 1096+300=1396 (1400). CAT D 1253 (5D) TOWER (18-001672) 391140.00N/0863311.00W, 1253+300+50 (AC)=1603 (1620). Radii: CAT A 1.30, CAT B 1.83, CAT C 2.89, CAT D 3.77.

Last Updated By: Charles Thibodeaux

Last Updated At: 2021-07-30 11:48:11.725884

Status: Verified **1/0243**

QUALITY
47
CHECKED

!FDC X/XXXX BMG IAP MONROE COUNTY, BLOOMINGTON, IN. RNAV (GPS) RWY 35, AMDT 1A... CIRCLING CAT D MDA 1620/HAA 774, VISIBILITY 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRE HAUTE RGNL ALTIMETER SETTING; INCREASE LPV DA TO 1165, LNAV/VNAV DA TO 1465 AND ALL MDA 140 FEET AND INCREASE LPV ALL CATS, LNAV CAT C, D VISIBILITY 1/4 SM, LNAV/VNAV ALL CATS AND CIRCLING C AND D VISIBILITY 1/2 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2. THIS IS RNAV (GPS) RWY 35, AMDT 1B. 2107301148-PERM

Digitally signed by
JASON KRETSCHMER
Sep 01, 2021