

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
JEEON	ONE	JEEON1.JEEON	NONE		
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	☐	☐	☒	☐	☒

DP ROUTE DESCRIPTION:

TAKEOFF RWY 13L: CLIMB ON HEADING 130.39 TO 977, THEN LEFT TURN DIRECT KAIMI AT OR BELOW 6000, THENCE...

TAKEOFF RWY 13R: CLIMB ON HEADING 130.40 TO 977, THEN LEFT TURN DIRECT KAIMI AT OR BELOW 6000, THENCE...

...THEN ON TRACK 088.90 TO CROSS JEEON AT OR ABOVE 4200, THEN ON ASSIGNED (TRANSITION). MAINTAIN ATC ASSIGNED ALTITUDE, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
BLYTHE	JEEON1.BLH	JEEON	TEEGE	TRACK 084.72	18.90	6600	6600	AT/ABOVE 11000
		TEEGE	BLH VORTAC	TRACK 082.89	59.03	7600	7600	
THERMAL	JEEON1.TRM	JEEON	TRM VORTAC	TRACK 120.74	10.18	3500	3500	

PBN REQUIREMENT NOTES:

RNAV 1 - GPS

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED

PROCEDURAL DATA NOTES:

TAKEOFF MINIMUMS:

RWY 13L: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 977.

RWY 13R: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 977.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARURE PROCEDURE (ODP).

CONTROLLING OBSTACLES:

RWY 13L: 1857 FT MSL AAO 334518.00N/1162721.00W

RWY 13R: 2044 FT MSL AAO 334503.00N/1162724.00W

MSA:

MSA FROM KPSP, 12800

LOST COMMUNICATIONS PROCEDURES:



ADDITIONAL FLIGHT DATA:
MAGVAR: KPSP 13E/1990.
DME/DME ASSESSMENT: UNSAT.
CHART: TOP ALTITUDE: ASSIGNED BY ATC.

AIRPORTS SERVED:	AIRPORT ID	CITY	STATE
	KPSP	PALM SPRINGS	CA

COMMUNICATIONS:
CHART: ATIS, CLNC DEL, GND CON, PALM SPRINGS ATCT.

FIXES AND/OR NAVAIDS:

REMARKS:
DO NOT CHART MOCA: FROM JEEON TO TEEGE, TEEGE TO BLH VORTAC, JEEON TO TRM VORTAC.

<u>FLIGHT INSPECTED BY</u>	<u>SIGNATURE</u> <i>Digitally signed by</i> ALLAN WILL Nov 15, 2024	<u>OFFICE</u> AJF	<u>DATE</u> 10/31/2024	
<u>DEVELOPED BY</u>	<u>SIGNATURE</u> <i>Digitally signed by</i> LEO PALMER Sep 20, 2024	<u>OFFICE</u> AJV-A421	<u>DATE</u> 08/05/2024	
<u>APPROVED BY</u>	<u>SIGNATURE</u> <i>Digitally signed by</i> ALLAN WILL Nov 15, 2024	<u>OFFICE</u> AJV-A421	<u>DATE</u> 02/20/2025	<u>TITLE</u> MANAGER
<u>REQUIRED EFFECTIVE DATE</u>				

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER:PSP ATCT, SOCAL APP CON, AMGR

CHANGES - REASONS:
ORIG.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME					NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
JEEON					ONE	JEEON1.JEEON	NONE		
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW13L (AER)	335006.60N/1163034.81W	N		-	-	-			
977 MSL	-	-	-	VA	143.39	-	AT/ABOVE 977		CG 500 FT PER NM TO 977
KAIMI	334524.43N/1162211.19W	Y	FB	DF	-	-	AT/BELOW 6000		LEFT TURN
RW13R (AER)*	335002.63N/1163041.60W*	N	-	-	-	-			*DISPL THLD (2999.74 FT)
977 MSL		-	-	VA	143.40	-	AT/ABOVE 977		CG 500 FT PER NM TO 977
KAIMI	334524.43N/1162211.19W	Y	FB	DF	-	-	AT/BELOW 6000		LEFT TURN
KAIMI	334524.43N/1162211.19W	Y	FB	IF	-	-	AT/BELOW 6000		
JEEON	334444.58N/1161825.26W	Y	FB	TF	101.90	03.21	AT/ABOVE 4200		
JEEON	334444.58N/1161825.26W	Y	-	IF	-	-	AT/ABOVE 4200		JEEON1.BLH
TEEGE	334209.84N/1155558.38W	Y	FB	TF	097.72	18.90	AT/ABOVE 11000		
BLH VORTAC	333545.83N/1144540.58W	Y	FB	TF	095.89	59.03			
JEEON	334444.58N/1161825.26W	Y	-	IF	-	-	AT/ABOVE 4200		JEEON1.TRM
TRM VORTAC	333741.15N/1160936.70W	Y	FB	TF	133.74	10.18			

