

[Print](#)

Project Name: UTA

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-21 14:15:45.371798

Status: Verified

IFDC 6/5622 UTA IAP TUNICA MUNI, TUNICA, MS. RNAV (GPS) RWY 17, AMDT 3B... LNAV/VNAV ALL CATS VISIBILITY 7/8. LNAV CATS A/B VISIBILITY 1, CATS C/D 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.24 NM TO RW17. CHANGE MIN ALT AT JOPGO TO READ: JOPGO/1.90 NM TO RW17 840. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MEM ALTIMETER SETTING; INCREASE LPV DA TO 468 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE LNAV/VNAV DA TO 545 FEET AND ALL VISIBILITIES 1/8 SM; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING MEM ALTIMETER SETTING. DELETE FOR INOPERATIVE ALS AND FOR INOPERATIVE ALS WHEN USING MEMPHIS ALTIMETER SETTING NOTES. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 17, AMDT 3C. 2604211415-PERM

Digitally signed by

CASEY D HILL

May 01, 2026

