Flight Procedures Cover Page	Task Action: FLIGHT CHECK	Task Type : IAP	Estimated Chart Date: 02/20/2025	APWS Task ID: 4E065920D82F4F91B980CFB0A9104837	APWS Project ID: 9333D72E652C4A1E8788851CE3691745		
Procedure: RNAV (RNP) Z RWY 16R ORIG	vocedure: Enroute: NAV (RNP) Z RWY 16R ORIG NO		Specialist: Christensen, Richard		Agreement Number:		
Airport ID: KSLC			Airport City: SALT LAKE CITY		State: UT		
Facility ID:	Facility Type:	Flight Inspection Remain New FC Slot	ark Type:				
Procedure Comments: ACTIVE DATA USED FOR AIRPORT AND I	RUNWAY.					OUAL IT	
ORIGINAL PROCEDURE.						20 CHECKER	
APPROVAL LETTER: MANDATORY ALTIT	QUALITY	201-					
WAIVER: DESCENT GRADIENT IN EXCES	38						
CONTACTS: ERIC SUSKI (AJV-A431), 405.954.7331 BEVERLY L. BORDY (AJV-A430), 405.954	.8293				NECKS		

						FIPC	BASIC	FOF	RM								
PROCEDURE:				A	AIRPORT NAME: A			AIR	AIRPORT ID:		SPECIAL CONTROL NO:						
RNAV (RNP) Z RWY 16R ORIG				S	SALT LAKE CITY INTL KS			KSI	KSLC		SG-11-076-24						
FAC ID: KSLC16F	RZ		CITY: SALT	LAKE CI	ГҮ	ST			ST:	ST: UT		ORIG CHART DATE: 02/20/2025					
DFL TYPE:	THIRD P	PARTY:	EST. TIME (ON SITE:	REIM	REIMB. NUMBER: PTS TASK ID:					•						
PROC/P		YES	3 0.4 4E065920D82F4F91B980C					980CFB0A	0CFB0A9104837								
					ł	PREF	LIGHT	NOT	ſES								
REVIEWER: anth	hony d vall	lera										DATE:	01/08/202	25			
COMMENTS:												CHECK (DNE:				
												X FLT (CK REQ		NFCR	RE J	JECT
																YES	NO
												CPV COM	IPLETE	?		Χ	
					PR	OCE	DURE I	RESU	ULTS	5							
INSPECTION DA	TE:	CREV	V #: N	#:	INSTRUMENT PROCEDURE STATUS: ARINC CODING:					íG:							
01/08/2025		VN21	.8 N	87	X	SAT	SAT W	//CHAN	NGES		SAT	X SA	Г	SAT	ſ/GOLD		NSAT
FLIGHT INSPEC	TOR SIGN	NATURE	2:		PR	PRINTED NAME: NOTAM INITIATED						FED?					
anthony d vallera @	01/08/202	25 20:25			VA	VALLERA, ANTHONY DOMINIC YES					XI	NO					
FLIGHT INSPEC	FOR REM	1ARKS:															
IN-FLIGHT OBSTACLE REPORT																	
OBSTRUCTION ID #: COORDINATES OR LOCATION: GNSS ALTITUDE (MSL): BAROMETRIC ALTITUDE (MSL): HEIGHT ABOVE GROUN					DUND LI	EVEL:											



AUTOMATED AL-365 RNAV (RNP) Z RWY 16R AUTOMATED AL-365 RNAV (RNP) Z RWY 16R

> SW-4 21 OCT 2024 COMPILER: CG REVIEWER: DBL CHKR: EFF: FIG



Memorandum

Date:	08/21/2024
To:	Wade Terrell, Manager, Flight Technologies and Procedures Division THRU: Wayne Radicke, Manager, Flight Procedures and Airspace Group
From:	Beverly L. Bordy, Manager, Team 3, AJV-A43
Subject:	Approval Request: SALT LAKE CITY INTL (KSLC), RNAV (RNP) Z RWY 16R

RNAV (RNP) Z RWY 16R SALT LAKE CITY INTL SALT LAKE CITY UT (KSLC)

8260.19J, paragraph 8-6-11n(1). Mandatory altitude in the intermediate segment.

Request approval to "Chart mandatory 11000 at LAWVA".

Salt Lake City TRACON (SF6) needs the 11000 crossing restriction at LAWVA due to the required separation needed to accommodate for SLC turn departures that depart underneath the arrivals from the west on the YUTES arrival.

Digitally signed by **ERIC N SUSKI** Nov 04, 2024

1. FLIGHT PROCEDURE IDENTIFICATION:

SALT LAKE CITY, UT SALT LAKE CITY INTL RNAV (RNP) Z RWY 16R

2. WAIVER REQUIRED AND APPLICABLE STANDARD:

FAAO Order 8260.3F, paragraph 2-5-3d. To permit intermediate segment descent gradients in excess of 318 feet per NM. The segment from BHIVE to the PFAF (BNKER) have a descent gradient of 321.92 and 322.0 feet per NM.

3. REASON FOR WAIVER (JUSTIFICATION FOR NONSTANDARD TREATMENT):

Request to publish the RNAV (RNP) Z RWY 16R using a descent gradient of 321.40 and 322.0 feet per NM from BHIVE to the PFAF (BNKER) which exceeds the maximum allowable descent gradient of 318.0 feet per NM. ATC has a requirement to ensure clearance of the 41st parallel due to separation of Hill AFB traffic and a need to remain at or above 7,500 FT MSL until 1.50 NM south. The intermediate segment is using the RNP AR RPCH - GPS (minimum RNP 1.0) throughout the intermediate segment to the PFAF.

4. EQUIVALENT LEVEL FOR SAFETY PROVIDED:

1. All initial and intermediate segments prior to BHIVE meets descent gradient criteria and provides ample time for aircraft to configure for final approach.

2. This is compliant with FAAO 8260.58C, para 3-1-4.b. that the PFAF is a Fly By (FB) fix.

3. The intermediate segment descent gradient and final approach segment length contribute to a stabilized approach.

4. Five (5) years of National Climatic Data Center (NCDC) data indicates the historical high temperature for two (2) months of each year (July and August) does not exceed 92.6°F/33.7°C.

5. ALTERNATIVE ACTIONS DEEMED NOT FEASIBLE:

1. Extending the intermediate segment length to meet descent gradient will infringe upon adjacent ATC established procedural separation measures currently in place and will cause a ripple affect on various sector's airspace.

6. COORDINATION WITH USER ORGANIZATIONS (SPECIFY):

AFS	
ZLC	
Department of Defense	e

7: SUBMITTED BY:

DATE	OFFICE IDENTIFICATION	TITLE	SIGNATURE	
8. AFS ACTIONS: APPROVED COMMENTS:	DISAPPROVED	NOT REQUIRI	ED	Digitally signed by ERIC N SUSKI Nov 04, 2024
DATE	ROUTING SYMBOL	SIGNATURE		







