FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE GRAPHIC DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL Altitudes are minimum altitudes unless otherwise indicated Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statue miles or feet RVR unless otherwise indicated.

_DP NAME				NUMBER FOUR	DP COMPUTER CODE JMAAL4.NAKED	SUPERSEDED NUMBER THREE	DATED 01/10/2013	ACTUAL EFFECTIVE DATE		
TYPE:			RNAV	FOOR			01/10/2013			
	\boxtimes									

DP ROUTE DESCRIPTION:

RWY 6: TURN RIGHT AS SOON AS PRACTICAL, CLIMB IN VISUAL CONDITIONS TO MNL NDB AT/ABOVE 1300, THEN ON MNL NDB BRG-236 TO OLLEO INT, THENCE ...

RWY 24: CLIMB DIRECT TO MNL NOB THEN ON MNL BRG-236 TO OLLEO INT, THENCE ...

...CONTINUE CLIMB TO AT/ABOVE 6000 ON JOH VOR/DME R-328 SOUTHBOUND TO JMAAL/JOH VOR/DME 25 DME, FLY JOH VOR/DME 25 DME ARC COUNTERCLOCKWISE TO NAKED/JOH VOR/DME R-273 25 DME.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	TRANSITION COMPUTER CODE	FROM FIX/NAVAID	<u>TO</u> <u>FIX/NAVAID</u>	COURSE	DISTANCE MEA	MOCA	CROSSING ALTITUDE/FIXES
-----------------	-----------------------------	--------------------	--------------------------------	--------	--------------	------	----------------------------

PBN REQUIREMENT NOTES:

EQUIPMENT REQUIREMENT NOTES:

ADF AND DME REQUIRED.

PROCEDURAL DATA NOTES:

NOTE: RWY 6 PROCEDURE NA AT NIGHT NOTE: RWY 6 VISUAL CONDITIONS MUST BE MAINTAINED UNTIL ESTABLISHED ON THE MNL NOB BEARING. NOTE: RAPIDLY RISING TERRAIN WEST-NORTHWEST TO EAST-NORTHEAST OF AIRPORT.

TAKEOFF MINIMUMS:

RWY 6: 1200-3 WITH MINIMUM CLIMB OF 460 FT/NM TO 6000 FROM MNL NDB. RWY 24: STANDARD WITH MINIMUM CLIMB OF 460 FT/NM TO 6000.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 24: TREES 469 FT FROM DER, 482FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/137 FT MSL. TREES 623 FT FROM DER, 385 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/130 FT MSL.

CONTROLLING OBSTACLES:

RWY 6, 24: 4528 FT TERRAIN 610637.40N/1464207.90W

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 24:12550 FT AAO 615653.90N/1470851.40W

MSA:

MSA FROM MNL NDB 060-250 8700, 250-060 12800

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

DP NAME JMAAL	<u>NUMBER</u> FOUR	DP COMPUTER CODE JMAAL4.NAKED	SUPERSEDED NUMBER THREE	DATED 01/10/2013	ACTUAL EFFECTIVE DATE
AIRPORTS SERVED:					07475
AIRPORT ID		CITY			STATE
PAVD		VALDEZ			AK

COMMUNICATIONS:

FIXES AND/OR NAVAIDS:

REMARKS:

100 FT TREES AND 200 FT SHIPS USED PER PUBLISHED PROCEDURES AT THE AIRPORT. WAIVER ON FILE: DME ARCS IN DEPARTURE ROUTE. WAIVER ON FILE: RWY 6 FLY VISUAL TO MNL NDB. WAIVER ON FILE: FOR NAMING CONVENTION, DUE TO DUPLICATE ENROUTE FIX ASSOCIATION.

ABBREVIATED AMENDMENT.

FLIGHT INSPECTED BY PROCESSED IAW TECHNICAL SUPPORT G SUBJECT: GUIDANCE FOR PROCEDURAL (SIGNATURE ROUP (AJF-17) MEMO DATED 07/07/2021, CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION	Digitally signed by DAVID DANNER Apr 17, 2025	OFFICE	DATE	
DEVELOPED BY LEO PALMER	SIGNATURE Digitally signed by LEO PALMER		OFFICE AJV-A421	DATE 4/6/2025	
APPROVED BY DAVE DANNER REQUIRED EFFECTIVE DATE	Apr 14, 2025 <u>SIGNATURE</u> Digitally signed by DAVID DANNER Apr 17, 2025		OFFICE AJV-A421	DATE 08/07/2025	<u>TITLE</u> MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

COORDINATED WITH:

CHANGES - REASONS:

- CANCELS T-NOTAM 3/8263. - DEPARTURE ROUTE DESCRIPTION COMMON ROUTE CHNAGED FROM "...CONTINUE CLIMB TO 6000" TO "...CONTINUE CLIMB TO AT/ABOVE 6000". PER FPT, SO AS NOT TO BE CONFUSD AS A HARD ALTITUDE.

- MSA ADDED FROM PUBLSIHED LDA PROCEDURE USING SAME NAVAID.

- RMEARKS: ADDED "100 FT TREES AND 200 FT SHIPS USED PER PUBLISHED PROCEDURES AT THE AIRPORT", AND ADDED THE WAIVERS ON FILE. FOR FUTURE PROCEDURE DEVELOPMENT CONSIDERATION.