

Print

Project Name: HYS ILS OR LOC RWY 34

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-20 17:55:19.698187

Status: Verified

!FDC 6/2614 HYS IAP HAYS RGNL, HAYS, KS. ILS OR LOC RWY 34, ORIG-F... S-LOC 34 CAT C VISIBILITY 5/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RSL ALTIMETER SETTING: INCREASE S-ILS 34 DA TO 2263 FEET; INCREASE ALL MDAS 80 FEET AND S-LOC 34 VISIBILITY CAT C 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. DELETE NOTE FOR INOPERATIVE MALSR WHEN USING RUSSELL ALTIMETER SETTING, INCREASE S-ILS ALL CATS VISIBILITY TO 1. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 34 CATS C/D VISIBILITY TO 1 SM. THIS IS ILS OR LOC RWY 34, ORIG-G. 2603201755-PERM

Digitally signed by
CASEY D HILL
Mar 24, 2026

