

PALM BEACH FOUR DEPARTURE

PALM BEACH INTL (PBI)
WEST PALM BEACH, FLORIDA

**TOP ALTITUDE:
ASSIGNED BY ATC**

RADAR and DME required.

PALM BEACH DEP CON
 128.3 317.4 (North)
 127.35 343.6 (South)
 D-ATIS
 123.75
 CLNC DEL
 121.6 284.6
 CPDLC
 GND CON
 121.9 284.6
 PALM BEACH TOWER
 119.1 257.8

ORLANDO
 112.2 ORL
 Chan 59

BAIRN

MATLK

WIXED

PERMT

PBI 75



SARASOTA
 117.0 SRQ
 Chan 117



JAYMC

CLEFF

PROTOTYPE-NOT
FOR NAVIGATION



PALM BEACH
 115.7 PBI
 Chan 104

SPNER

FREEPORT
 113.2 ZFP
 Chan 79

LEE COUNTY
 114.15 RSW
 Chan 88(Y)

SWAGS

VIRGINIA KEY
 117.1 VKZ
 Chan 118

FORT LAUDERDALE
 114.4 FLL
 Chan 91

TAKEOFF MINIMUMS

Rwy 14, 32: Standard.

Rwy 10L: Standard with minimum climb of 720'/NM to 416.
 Takeoff must occur no later than 2000' prior to DER.
 Do not exceed 210K until established north-northwest bound.

Rwy 10R: Standard with minimum climb of 350'/NM to 414. Do not exceed 150K until established south-southwest bound.

Rwy 28L/R: Standard with minimum climb of 210'/NM to 1800.

NOTE: Chart not to scale.



DEPARTURE ROUTE DESCRIPTION

TAKEOFF ALL RUNWAYS: Climb on assigned heading for RADAR vectors to filed or assigned route. Maintain ATC assigned altitude. Expect filed altitude 10 minutes after departure.

PALM BEACH FOUR DEPARTURE