

Flight Procedures Cover Page	Task Action: FLIGHT CHECK	Task Type: Textual DP	Estimated Chart Date: 10/29/2026	APWS Task ID: 60ED620D9DC44F5980BC9932511D1CE2	APWS Project ID: BD71107627F64840B95F30144F383532
Procedure: TAKEOFF MINIMUMS AND OBSTACLE DP AMDT 1		Enroute: NO	Specialist: Townsend, Matthew		Agreement Number:
Airport ID: KEBD			Airport City: WILLIAMSON		State: WV
Facility ID:	Facility Type:	Flight Inspection Remark Type: New FC Slot			
Procedure Comments: UTILIZED ACTIVE AIRNAV DATA FOR AIRPORT AND RUNWAY 8 AND 26. UPDATED TAKE OFF MINIMUMS FOR RWY 8 AND 26. PROCEDURE NA AT NIGHT NOTE RETAINED PER FPT. CONTACT ROBERT HAMILTON, AJV-A433, 405-954-4608. QUALITY 23 CHECKED					

26078

WILKES-BARRE/SCRANTON, PA (CON'T)

WILKES-BARRE WYOMING VALLEY (WBW)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG 26JUL12 (12208) (FAA)

TAKEOFF MINIMUMS:

- Rwy 7, std. w/min. climb of 280' per NM to 3300, or 2400-3 for climb in visual conditions.
- Rwy 9, std. w/min. climb of 307' per NM to 2600, or 2400-3 for climb in visual conditions.
- Rwy 25, std. w/min. climb of 320' per NM to 3100, or 2400-3 for climb in visual conditions.
- Rwy 27, 1000-3 w/min. climb of 415' per NM to 2200, or 2400-3 for climb in visual conditions.

DEPARTURE PROCEDURE:

- Rwy 7, climb heading 066° to 3300 before proceeding on course or for climb in visual conditions cross Wilkes-Barre Wyoming Valley airport at or above 2800 before proceeding on course.
- Rwy 9, climb heading 089° to 2800 before proceeding on course or for climb in visual conditions cross Wilkes-Barre Wyoming Valley airport at or above 2800 before proceeding on course.
- Rwy 25, climb heading 246° to 3100 before proceeding on course or for climb in visual conditions cross Wilkes-Barre Wyoming Valley airport at or above 2800 before proceeding on course.
- Rwy 27, climb heading 269° to 2700 before proceeding on course or for climb in visual conditions cross Wilkes-Barre Wyoming Valley airport at or above 2800 before proceeding on course.

TAKEOFF OBSTACLE NOTES:

- Rwy 7, road beginning 182' from DER, 428' right of centerline, up to 15' AGL/579' MSL.
- Trees and poles beginning 409' from DER, 32' left of centerline, up to 99' AGL/659' MSL.
- Trees and poles beginning 639' from DER, 309' right of centerline, up to 100' AGL/699' MSL.
- Dike 751' from DER, right and left of centerline, 0' AGL/564' MSL.
- Building 3071' from DER, 873' left of centerline, up to 80' AGL/ 640' MSL.
- Mobile crane 4526' from DER, up to 120' AGL/660' MSL.
- High tension power pole 6003' from DER, 1843' right of centerline, up to 173' AGL/719' MSL.
- Rwy 9, trees beginning 39' from DER, 47' right of centerline, up to 111' AGL/651' MSL.
- Trees beginning 104' from DER, 344' left of centerline, up to 100' AGL/640' MSL.
- Buildings beginning 1.44 NM from DER, 2517' right of centerline, up to 58' AGL/918' MSL.
- Rwy 25, road beginning 17' from DER, 435' left of centerline, up to 15' AGL/577' MSL.
- Trees beginning 553' from DER, 103' left of centerline, up 134' AGL/634' MSL.
- Trees beginning 1668' from DER, 36' right of centerline, up to 107' AGL/647' MSL.
- Tower 1.23 NM from DER, 1297' right of centerline, 203' AGL/753' MSL.
- Rwy 27, trees 539' from DER, 380' left of centerline, up to 117' AGL/557' MSL.
- Trees beginning 1285' from DER, left and right of centerline, up to 107' AGL/647' MSL.
- Poles and trees beginning 1.18 NM from DER, 957' right of centerline, up to 52' AGL/1352' MSL.

WILLIAMSON, WV

SOUTHERN WEST VIRGINIA RGNL (EBD)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

ORIG-A 26JUL12 (22307) (FAA)

TAKEOFF MINIMUMS:

- Rwy 8, 500-2¼.
- Rwy 26, 300-2.

NOTE: NA at night.

DEPARTURE PROCEDURE:

- Rwy 8, climb heading 077° to 2700 before proceeding on course.
- Rwy 26, climb heading 257° to 2400 before proceeding on course.

TAKEOFF OBSTACLE NOTES:

- Rwy 8, trees and high terrain beginning at DER, 77' right of centerline, up to 100' AGL/1998' MSL.
- Trees beginning 347' from DER, 185' left of centerline, up to 100' AGL/1998' MSL.
- Rwy 26, trees beginning 11' from DER, 35' left of centerline, up to 100' AGL/1927' MSL.
- Trees beginning 864' from DER, 79' right of centerline, up to 100' AGL/1998' MSL.

WILLIAMSPORT, PA

WILLIAMSPORT RGNL (IPT)

TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES

AMDT 6 22JUN17 (17173) (FAA)

TAKEOFF MINIMUMS:

- Rwy 9, std. w/min. climb of 300' per NM to 1500 or 2800-3 VCOA.
- Rwy 12, std. w/min. climb of 475' per NM to 1000 or 2800-3 VCOA.
- Rwy 27, std. w/min. climb of 470' per NM to 1000 or 2800-3 VCOA.
- Rwy 30, std. w/min. climb of 375' per NM to 1500 or 2800-3 VCOA.

DEPARTURE PROCEDURE:

- Rwy 9, climb heading 087° to 2600 before proceeding on course.
- Rwy 12, climbing left turn heading 090° to 2500 before proceeding on course.
- Rwy 27, climbing right turn heading 285° to 2800 before proceeding on course.
- Rwy 30, climb heading 296° to 2500 before proceeding on course.

VCOA:

- All Rwys, Obtain ATC approval for VCOA when requesting IFR clearance. Climb in visual conditions to cross Williamsport RGNL Airport at or above 2800 before proceeding on course.

CON'T

26078

16 APR 2026 to 14 MAY 2026

4 MAY 2026 to 16 APR 2026