

[Print](#)

Project Name: OOA

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-13 13:22:29.372853

Status: Verified

!FDC 6/1508 OOA IAP OSKALOOSA MUNI, OSKALOOSA, IA. RNAV (GPS) RWY 13, AMDT 1A... LNAV CAT C VISIBILITY 1 1/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT CIPON TO READ: CIPON/3.00 NM TO RW13 1820. CHANGE CHART VDP TO READ: CHART VDP AT 1.13 NM TO RW13. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OTM ALTIMETER SETTING: INCREASE LPV DA TO 1212 FEET; INCREASE LNAV/VNAV DA TO 1238 FEET; INCREASE ALL MDAS 20 FEET. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING OTM ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. THIS IS RNAV (GPS) RWY 13, AMDT 1B. 2604131322-PERM

Digitally signed by

CASEY D HILL

Apr 14, 2026

