

[Print](#)

Project Name: SNY RNAV (GPS) RWY 13

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-20 12:12:22.440726

Status: Verified

!FDC 6/7322 SNY IAP SIDNEY MUNI/LLOYD W CARR FLD, SIDNEY, NE. RNAV (GPS) RWY 13, AMDT 2B... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE CHART VDP NOTE TO READ: CHART VDP AT 1.38 NM TO RW13. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE IBM ALTIMETER SETTING: INCREASE LPV DA TO 4722 FEET AND ALL VISIBILITIES 3/8 SM; INCREASE ALL MDAS 160 FEET AND LNAV VISIBILITY CAT C 1/2 SM, LNAV VISIBILITY CAT D 3/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/2 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING IBM ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 13, AMDT 2C. 2604201212-PERM

Digitally signed by

CASEY D HILL

May 04, 2026

