


WAAS CH 82031 W27A	APP CRS 294°	Rwy Idg 7500 TDZE 53 APT Elev 53
--	------------------------	---

RNP APCH - GPS.	MALSRL 	MISSED APPROACH:CLIMB TO 600 THEN CLIMBING LEFT TURN TO 3000 DIRECT CORVA AND HOLD.
CIRCLING TO RWY 16, 34 NA AT NIGHT. CHART NOTE: CIRCLING NA NORTH OF RWY 9-27. VDP NA WHEN USING VZD/PAVD ALTIMETER SETTING. BARO-VNAV NA. FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO RVR 4500, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8, LNAV CATS C/D VISIBILITY TO RVR 6000. WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VDZ/PAVD ALTIMETER SETTING AND INCREASE LPV DA TO 434 FEET AND ALL VISIBILITIES TO RVR 3500; INCREASE LNAV/VNAV DA TO 629 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C/D TO RVR 5500.		

PROTOTYPE-NOT FOR NAVIGATION

