

[Print](#)

Project Name: BMG circling radii increase

Project Reason: Order 8260.3, chapter 2, new circling criteria applied. Only circling minimums verified. Backup altimeter and alternate minimums note updated as required. Controlling obstacles: CAT A 1069 (2C) TREE 390958.69N/0863736.05W, 1069+300=1369 (1380). CAT B/C 1096 (1C) TREE (18-021837) 391047.82N/0863628.31W, 1096+300=1396 (1400). CAT D 1253 (5D) TOWER (18-001672) 391140.00N/0863311.00W, 1253+300+50 (AC)=1603 (1620). Radii: CAT A 1.30, CAT B 1.83, CAT C 2.89, CAT D 3.77.

Last Updated By: Charles Thibodeaux

Last Updated At: 2021-07-30 14:48:51.920783

Status: Verified **1/0245**



IFDC X/XXXX BMG IAP MONROE COUNTY, BLOOMINGTON, IN. ILS OR LOC/DME RWY 35, AMDT 6B... CIRCLING CAT D MDA 1620/HAA 774, VISIBILITY 2 1/2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRE HAUTE RGNL ALTIMETER SETTING; INCREASE S-ILS 35 DA TO 1165 AND ALL MDA 140 FEET AND INCREASE S-ILS 35 ALL CATS VISIBILITY 1/4 SM, S-LOC 35 CAT C AND D AND CIRCLING CAT C AND D VISIBILITY 1/2 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2. THIS IS ILS OR LOC/DME RWY 35, AMDT 6C. 2107301448-PERM

*Digitally signed by*

**JASON KRETSCHMER**

Sep 01, 2021