

Print

Project Name: MUT

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-08 17:36:03.110271

Status: Verified

!FDC 6/0966 MUT IAP MUSCATINE MUNI, MUSCATINE, IA. RNAV (GPS) RWY 6, ORIG-B... LNAV CAT C VISIBILITY 1 5/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE IOW ALTIMETER SETTING: INCREASE LPV DA TO 1147 FEET; INCREASE LNAV/VNAV DA TO 1303 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING IOW ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 6, ORIG-C. 2604081736-PERM

Digitally signed by
CASEY D HILL
Apr 14, 2026

