

Print

Project Name: LSE

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-31 14:36:43.62655

Status: Verified

IFDC 6/9737 LSE IAP LA CROSSE RGNL, LA CROSSE, WI. RNAV (GPS) RWY 36, ORIG-D... LNAV CAT C VISIBILITY 1 3/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. DELETE *LNAV ONLY. CHANGE CHART VDP TO READ: CHART VDP AT 1.45 NM TO RW36. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ONA ALTIMETER SETTING: INCREASE LPV DA TO 1007 FEET; INCREASE LNAV/VNAV DA TO 1257 FEET; INCREASE ALL MDAS 60 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CAT B 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING ONA ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 36, ORIG-E. 2603311436-PERM

Digitally signed by
CASEY D HILL
Apr 10, 2026

