

Print

Project Name: 7L2 CLEAR T-NOTAMS

Project Reason: CLEAR T-NOTAMS FOR RNAV (GPS) RWY 9 AND RNAV (GPS) RWY 27 FOR NEW MSA CONTROLLING OBSTACLE 2864 MSL/599 AGL WINDMILL (2024-WTE-916-OE) 461250.65N/0993557.99W (4D). CLEAR T-NOTAM FOR RNAV (GPS) RWY 9 CIRCLING CAT A/B MIN INCREASE. CONTROLLING OBSTACLE CAT A 2010 MSL TREE 461151.00N/1001406.00W (4B). CONTROLLING OBSTACLE CAT B 2095 MSL TREE 461124.00N/1001515.00W (4B).UPDATE NOTES ON BOTH PROCEDURES.

Last Updated By: Leo Palmer

Digitally signed by

DAVID DANNER

Last Updated At: 2025-03-03 16:05:56.87252

Mar 03, 2025

Status: Active

!FDC 5/8572 7L2 IAP LINTON MUNI, LINTON, ND. RNAV (GPS) RWY 27, ORIG-C... MSA FROM RW27 25NM 3900. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH - GPS. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BIS ALTIMETER SETTING AND INCREASE ALL DA 107 FEET AND VISIBILITY LPV AND LNAV/VNAV ALL CATS 1/4 SM; INCREASE ALL MDA 120 FEET AND VISIBILITY LNAV CAT C 1/4 SM. CHANGE NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING BIS ALTIMETER SETTING. DELETE PROFILE NOTE: *LNAV ONLY. DELETE ASTERISK IN PROFILE AT CISOX AND VDP. THIS IS RNAV (GPS) RWY 27, ORIG-D. 2503031605-PERM

