

[Print](#)

Project Name: MKO

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-04-01 20:03:13.339084

Status: Verified

!FDC 6/9772 MKO IAP MUSKOGEE-DAVIS RGNL, MUSKOGEE, OK. RNAV (GPS) RWY 13, ORIG-D... LNAV CAT C VISIBILITY 1 5/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT HENBI TO READ: HENBI/3.00 NM TO RW13 1620. CHANGE CHART VDP TO READ: CHART VDP AT 1.64 NM TO RW13. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TQH ALTIMETER SETTING: INCREASE LPV DA TO 948 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE LNAV/VNAV DA TO 1233 FEET; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, CIRCLING VISIBILITY CAT C 1/4 SM, AND CIRCLING VISIBILITY CAT D 1/2 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING TQH ALTIMETER SETTING. CHANGE FOR UNCOMPENSATED BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 53C. CHANGE RWY 4, 18, 22, 36 HELICOPTER VISIBILITY REDUCTION NOTE TO READ: RWY 13 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 13, ORIG-E. 2604012003-PERM

Digitally signed by
CASEY D HILL
Apr 10, 2026

