

[Print](#)

Project Name: FRG

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-16 18:11:25.349219

Status: Verified

!FDC 6/1140 FRG IAP REPUBLIC, FARMINGDALE, NY. RNAV (GPS) Y RWY 14, AMDT 2G... LNAV CATS C/D VISIBILITY 1 1/8. CHART NOTE: RWY 14 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ISP ALTIMETER SETTING: INCREASE LPV DA TO 374 FEET; INCREASE LNAV/VNAV DA TO 442 FEET; INCREASE ALL MDAS 40 FEET AND LNAV VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. THIS IS RNAV (GPS) Y RWY 14, AMDT 2H. 2603161811-PERM

Digitally signed by
CASEY D HILL
Mar 19, 2026

