

Print

Project Name: GNV RNAV (GPS) RWY 7

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-18 14:49:36.887396

Status: Verified

!FDC 6/1148 GNV IAP GAINESVILLE RGNL, GAINESVILLE, FL. RNAV (GPS) RWY 7, AMDT 1B... LNAV CAT C VISIBILITY 1 3/8. DELETE NOTE DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE OCF ALTIMETER SETTING AND INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C 1/4 SM, LNAV VISIBILITY CAT D 1/8 SM, AND CIRCLING VISIBILITY CATS C/D 1/2 SM. CHANGE VDP NA NOTE TO READ: VDP NA WHEN USING OCF ALTIMETER SETTING. CHANGE VISIBILITY REDUCTION BY HELICOPTER NOTE TO READ: RWY 7 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. THIS IS RNAV (GPS) RWY 7, AMDT 1C. 2603181449-PERM

Digitally signed by  
**CASEY D HILL**  
Mar 19, 2026

