

[Print](#)

Project Name: CWF

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-02-27 16:30:41.586586

Status: Verified

!FDC 6/3931 CWF IAP CHENNAULT INTL, LAKE CHARLES, LA. RNAV (GPS) RWY 15, AMDT 1A... LNAV CATS C/D VISIBILITY 7/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LCH ALTIMETER SETTING: INCREASE LPV DA TO 233 FEET; INCREASE LNAV/VNAV DA TO 524 FEET; INCREASE ALL MDAS 20 FEET AND LNAV VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CAT D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING LCH ALTIMETER SETTING. DELETE NOTE: FOR INOPERATIVE ALS WHEN USING LAKE CHARLES RGNL ALTIMETER SETTING INCREASE LNAV/VNAV VISIBILITY ALL CATS TO 1 3/8 SM. THIS IS RNAV (GPS) RWY 15, AMDT 1B. 2602271630-PERM

Digitally signed by
CASEY D HILL
Mar 05, 2026

QUALITY
6
CHECKED