

Print

Project Name: GLY

Project Reason: Visibility Initiative (Garmin) - Update IAP visibility minimums IAW Order 8260.3, Chapter 3, Section 3-3. Visibility Minimums.

Last Updated By: Timothy Johnson

Last Updated At: 2026-03-17 19:37:54.567835

Status: Verified

!FDC 6/1141 GLY IAP CLINTON RGNL, CLINTON, MO. RNAV (GPS) RWY 18, ORIG-B... LNAV CATS C/D VISIBILITY 1 1/8. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH – GPS. DELETE *LNAV ONLY. CHANGE MIN ALT AT IPIWO TO READ: IPIWO/1.70 NM TO RW18 1380. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE SZL ALTIMETER SETTING: INCREASE LPV DA TO 1121 FEET; INCREASE LNAV/VNAV DA TO 1121 FEET; INCREASE ALL MDAS 80 FEET AND LNAV VISIBILITY CATS C/D 1/4 SM AND CIRCLING VISIBILITY CAT D 1/4 SM. CHANGE BARO-VNAV AND VDP NA NOTES TO READ: BARO-VNAV AND VDP NA WHEN USING SZL ALTIMETER SETTING. THIS IS RNAV (GPS) RWY 18, ORIG-C. 2603171937-PERM

Digitally signed by
CASEY D HILL
Mar 19, 2026

