FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE **GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated

			Ce	eilings are in feet abov	e airport elevat	ion. Distances are i	n nautical miles. Visibilities are in statue r	niles or feet RVR unless otherwise indicated.		
DP NAM	<u>E</u>					NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	ACTUAL EFFECTIVE DATE
ILLS						THREE	LILLS3.LILLS	TWO	01/03/19	
TYPE:	OBSTACLE	COPTER	SID	SPECIAL	RNAV					
	E DESCRIPTIO TTE/DOUGLAS									
		` ,	G 182 96 TO	1260 THEN OF	N HEADING	182 96 OR AS	S ASSIGNED BY ATC ON RAD	AR VECTORS TO LAMDE, THEN	CF	
				,				AR VECTORS TO LAMDE, THEN		
				,				AR VECTORS TO LAMDE, THEN		
				,				AR VECTORS TO LAMDE, THEN		
				,				AR VECTORS TO LAMDE, THEN AR VECTORS TO LAMDE, THEN		
			0 002.07 . 0	00, 0.		0_0.00			-	
ON E	EPICTED ROU	TE TO LILLS. MA	UNTAIN 8000). EXPECT CLE	ARANCE T	O FILED ALTII	TUDE WITHIN 10 MINUTES AF	TER DEPARTURE		
CONCOR	D-PADGETT R	GNI (KJQF):								
		B ON HEADING ()16.46 TO 22	00, THEN ON H	IEADING A	SSIGNED BY A	ATC, THENCE			
TAKEOF	F RWY 20: CLIM	IBING LEFT TUR	RN HEADING	150.00 TO 240	0, TTHEN C	ON HEADING A	ASSIGNED BY ATC, THENCE			
2ASTON	IA MUNI (KAKH	1/-								
	`	,)49.34 TO 27	00 BEFORE TU	RNING LEI	T, THEN ON F	HEADING ASSIGNED BY ATC,	THENCE		
TAKEOF	F RWY 21: CLIM	IB ON HEADING	214.33 TO 1	600 BEFORE P	ROCEEDIN	IG [°] NORTH, TH	IEN ON HEADING ASSIGNED	BY ATC, THENCE		
INICOLA	ITON LINCOLN	COUNTY DON	(KID I).							
		COUNTY RGNL	` '	00 BEFORE PR	OCEEDING	S ON COURSE	E. THEN ON HEADING ASSIGN	IED BY ATC. THENCE		
							HEADING ASSIGNED BY ATO			
		(5115)								
	OLINA RGNL (I	KRUQ): B ON HEADING A	ASSIGNED B	Y ATC THENC	F					
				-,		GHT, THEN O	N HEADING ASSIGNED BY AT	C, THENCE		
						•		•		
ON RA	DAR VECTORS	TO LAMDE, THE	EN ON DEPI	CTED ROUTE T	O LILLS. M	AINTAIN 3000	. EXPECT CLEARANCE TO FIL	LED ALTITUDE WITHIN 10 MINU	TES AFTER DEPAR	ture.

DEPARTING CHARLOTTE-MONROE EXECUTIVE (KEQY), LANCASTER COUNTY-MC WHIRTER FIELD (KLKR), STANLY COUNTY (KVUJ), AND ROCK HILL/YORK CO/BRYANT FIELD (KUZA): CLIMB ON HEADING ASSIGNED BY ATC, ON RADAR VECTORS TO LAMDE, THEN ON DEPICTED ROUTE TO LILLS. MAINTAIN 3000. EXPECT CLEARANCE TO FILED ALTITUDE WITHIN 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

TRANSITION NAME	<u>TRANSITION</u>	<u>FROM</u>	<u>TO</u>	COURSE	DISTANCE MEA	MOCA	CROSSING
IRANSIIION NAME	COMPUTER CODE	FIX/NAVAID	FIX/NAVAID	COURSE	DISTANCE MEA	IVIOCA	ALTITUDE/FIXES

PROCEDURAL DATA NOTES:

NOTE: FOR TURBO JETS ONLY.

NOTE: TRANSPONDER CODE WILL BE ISSUED VIA PDC OR CHARLOTTE CLNC DEL.

NOTE: IF UNABLE TO ACCEPT CLIMB RATES, ADVISE ATC ON INITIAL CONTACT.

NOTE: CHARLOTTE/DOUGLASS INTL ONLY: ACCELERATE TO 250 KIAS, IF UNABLE ADVISE ATC. UPON REACHING 10000 MSL, ACCELERATE TO AND MAINTAIN 280 KIAS, IF UNABLE ADVISE ATC.

<u>DP NAME</u>

<u>NUMBER</u>
<u>DP COMPUTER CODE</u>
<u>SUPERSEDED NUMBER</u>
<u>DATED</u>
<u>ACTUAL EFFECTIVE DATE</u>

LILLS THREE LILLS3.LILLS TWO 01/03/19

NOTE: ALL OTHER AIRPORTS: UPON REACHING 10000 MSL. ACCELERATE TO AND MAINTAIN 280 KIAS. IF UNABLE ADVISE ATC.

PBN REQUIREMENTS NOTES:

RNAV 1 - DME/DME/IRU OR GPS.

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

TAKEOFF MINIMUMS:

CHARLOTTE/DOUGLAS INTL (KCLT):

RWY 18C, 18L, 18R, 36C, 36R: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1260.

RWY 36L: STANDARD WITH MINIMUM CLIMB OF 500 FT PER NM TO 1400.

CONCORD-PADGETT RGNL (KJQF):

RWY 2: STANDARD.

RWY 20: STANDARD WITH MINIMUM CLIMB OF 320 FT PER NM TO 2400.

GASTONIA MUNI (KAKH);

RWY 3, 21: STANDARD.

CHARLOTTE-MONROE EXECUTIVE (KEQY):

RWY 5. 23: STANDARD.

LINCOLNTON-LINCOLN COUNTY RGNL (KIPJ):

RWY 5. 23: STANDARD.

LANCASTER COUNTY-MC WHIRTER FIELD (KLKR):

RWY 6, 24: STANDARD.

STANLY COUNTY (KVUJ):

RWY 4L. 22R: NA - ENVIRONMENTAL.

RWY 22L: STANDARD

RWY 4R: 300-1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 315 FT PER NM TO 1000.

MID-CAROLINA RGNL (KRUQ):

RWY 2: STANDARD.

RWY 20: 400-2 3/4 OR STANDARD WITH MINIMUM CLIMB OF 205 FT PER NM TO 1300, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1200 FT PRIOR TO DER.

ROCK HILL/YORK CO/BRYANT FIELD (KUZA):

RWY 2, 20: STANDARD.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

CHARLOTTE/DOUGLAS INTL (KCLT):

RWY 36L: 2748 FT MSL TOWER 352145.00N/0810918.00W.

CONCORD-PADGETT RGNL (KJQF):

RWY 20: 1950 FT MSL TOWER 351715.00N/0804144.00W.

STANLY COUNTY (KVUJ):

RWY 4R: 732 FT MSL TREE (37-111225) 352557.53N/0800829.12W (CLIMB GRADIENT), 803 FT MSL TREE (37-112801) 352620.07N/0800816.77W (CLIMB TO ALTITUDE), 820 FT MSL TREE (37-116182)

OVALITY 48 CHECKER <u>DP NAME</u>
LILLS

NUMBER

DP COMPUTER CODE
SUPERSEDED NUMBER
DATED
ACTUAL EFFECTIVE DATE
LILLS TWO
01/03/19

352627.52N/0800810.70W (CEILING), 790 FT MSL (37-114938) 352637.40N/0800804.59N (VISIBILITY).

MID-CAROLINA RGNL (KRUQ):

RWY 20: 1121 FT MSL TOWER 353613.00N/0803234.12W.

MSA:

KCLT MSA FROM KCLT 3800.
KJQF MSA FROM KJQF 3800.
KAKH MSA FROM KAKH 3800.
KEQY MSA FROM KEQY 3100.
KIPJ MSA FROM KIPJ 3800.
KLKR MSA FROM KLKR 2300.
KVUJ MSA FROM KVUJ 3100.
KRUQ MSA FROM KRUQ 3400.

KUZA MSA FROM KUZA 3800.

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

AIRPORT MV: KCLT (P) 7W/2000, KJQF 6W/1995, KAKH 6W/2000, KEQY 6W/1990, KIPJ 6W/1995, KLKR 7W/2000, KVUJ 6W/1985, KRUQ 6W/1985, KUZA 5W/1990.

DME/DME ASSESSMENT: SAT (RNP 2.0)

CHARLOTTE/DOUGLAS INTL - CHART: TOP ALTITUDE 8000 **CONCORD-PADGETT RGNL - CHART:** TOP ALTITUDE 3000.

GASTONIA MUNI - CHART: TOP ALTITUDE 3000.

CHARLOTTE-MONROE EXECUTIVE - CHART: TOP ALTITUDE 3000.
LINCOLNTON-LINCOLN COUNTY RGNL - CHART: TOP ALTITUDE 3000.
LANCASTER COUNTY-MC WHIRTER FIELD - CHART: TOP ALTITUDE 3000.

STANLY COUNTY - CHART: TOP ALTITUDE 3000.
MID-CAROLINA RGNL - CHART: TOP ALTITUDE 3000.

ROCK HILL/YORK CO/BRYANT FIELD - CHART: TOP ALTITUDE 3000.

CHART NOTE: (CHARLOTTE/DOUGLAS INTL ONLY) SEE ADDITIONAL REQUIREMENTS ON AAUP

AIRPORTS SERVED:

7 til til Olt i O O Ditt v D Di		
AIRPORT ID	CITY	STATE
KCLT	CHARLOTTE	NC
KJQF	CONCORD	NC
KAKH	GASTONIA	NC
KEQY	MONROE	NC
KIPJ	LINCOLNTON	NC
KLKR	LANCASTER	SC
KVUJ	ALBEMARLE	NC
KRUQ	SALISBURY	WALIT
		48

<u>DP NAME</u> LILLS	<u>NUMBER</u> THREE	DP COMPUTER CODE LILLS3.LILLS	SUPERSEDED NUMBER TWO	DATED 01/03/19	ACTUAL EFFECTIVE DATE
KUZA		ROCK HILL			SC

COMMUNICATIONS:

CHARLOTTE/DOUGLAS INTL: CHART: ATIS, CLNC DEL, GND CON, TOWER.

CONCORD-PADGETT RGNL: CHART: ATIS, CLNC DEL, GND CON, TOWER, UNICOM.

GASTONIA MUNI: CHART: ASOS, CLNC DEL. UNICOM.

CHARLOTTE-MONROE EXECUTIVE: CHART: ASOS, CLNC DEL, UNICOM.

LINCOLNTON-LINCOLN COUNTY RGNL: CHART: AWOS, CLNC DEL (GCO), UNICOM.

LANCASTER COUNTY-MC WHIRTER FIELD: CHART: AWOS, GCO, UNICOM.

STANLY COUNTY: CHART: ATIS, CLNC DEL, GND CON, TOWER. MID-CAROLINA RGNL: CHART: AWOS. CLNC DEL. UNICOM.

ROCK HILL/YORK CO/BRYANT FIELD: CHART: ASOS, CLNC DEL, UNICOM

FIXES AND/OR NAVAIDS:

REMARKS:

- CONCORD-PADGETT RGNL RWY 20 CLIMB GRADIENT ROUNDED TO 320 FT PER NM FOR PUBLICATION (COMPUTED VALUE 317 FT PER NM).
- 2. MID-CAROLINA RGNL COUNTY RWY 20 CLIMB GRADIENT ROUNDED TO 205 FT PER NM FOR PUBLICATION (COMPUTED VALUE 202 FT PER NM).
- 3. ABBREVIATED AMENDMENT.

Digitally signed by

 FLIGHT INSPECTED BY
 CASEY D HILL
 OFFICE
 DATE

 JEFFREY ECKMAN
 Feb 06, 2024
 FPO
 09/15/2023

DEVELOPED BY

Digitally signed by

ANA Y VEGA

ANA Y VEGA
Feb 06, 2024
AJV-A412
O1/06/2023

Digitally signed by

 APPROVED BY
 CASEY D HILL
 OFFICE
 DATE
 TITLE

 JULIE MORGAN
 Feb 06, 2024
 AJV-A410
 MANAGER

REQUIRED EFFECTIVE DATE

ROUTINE

ANA VEGA

COORDINATED WITH:

CHANGES - REASONS:

- 1. REMOVED ALL REFERENCES TO KCLT RWY 5/23 INCORPORATE NOTAM CLT 05/427.
- 2. TAKEOFF MINIMUMS: STANLY COUNTY (KVUJ) AMENDED RWY 4R FROM "300 1 ½ OR STANDARD WITH MINIMUM CLIMB OF 276 FT PER NM TO 1000" TO "300-1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 315 FT PER NM TO 1000" INCORPORATE FDC 3/0577.
- 3. TAKEOFF MINIMUMS: STANLY COUNTY (KVUJ) RWY 4L, 22R UPDATED TO READ "NA ENVIRONMENTAL" PER AIRNAV USED AS ASSAULT STRIP BY MILITARY, IT IS NOT USED FOR IFR OPERATIONS.
- 4. CONTROLLING OBSTACLES: STANLY COUNTY (KVUJ) RWY 4R UPDATED FROM "837 FT MSL TREE 352627.34N/0800808.17W" TO "732 FT MSL TREE (37-111225) 352557.53N/0800829.12W (CLIMB GRADIENT) AND ADDED "803 FT MSL TREE (37-112801) 352620.07N/0800816.77W (CLIMB TO ALTITUDE), 820 FT MSL TREE (37-116182) 352627.52N/0800810.70W (CEILING), 790 FT MSL (37-114938) 352637.40N/0800804.59N (VISIBILITY)."AND CHARLOTTE/DOUGLAS INTL (KCLT) UPDATED RWY 36L TO "2748 FT MSL TOWER 352145.00N/0810918.00W NEW PENETRATING OBSTACLES.
- 5. CONTROLLING OBSTACLES: REMOVED ALL "ROUTE DEVELOPMENT" OBSTACLES ROUTE ISN'T BASED ON OBSTACLES.
- 6. COMBINED NOTES "RNAV 1" AND "DME/DME/IRU OR GPS REQUIRED" TO READ "RNAV 1 DME/DME/IRU OR GPS REQUIRED" AND MOVED TO PBN REQUIREMENTS NOTES IAW 8260.46J 2-1-1F (6) AND APPENDIX E, SECTION 1 PARA 5 MEMO.
- 7. PROCEDURAL DATA NOTES: MOVED RADAR REQUIRED NOTE TO EQUIPMENT REQUIREMENT NOTES IAW 8260.46J 2-1-1 F (5).
- 8. PROCEDURAL DATA NOTES: REPLACED "TURBOJETS ONLY" WITH "TURBO JETS ONLY" IAW 8260.46J APP E, SEC 1, PARA 2G.

<u>DP NAME</u>
LILLS

NUMBER

DP COMPUTER CODE
SUPERSEDED NUMBER
DATED
ACTUAL EFFECTIVE DATE
LILLS TWO
01/03/19

- 9. ADDITIONAL FLIGHT DATA: REMOVED "REFERENCE PILOT NAVIGATION AREA" NO LONGER REQUIRED PER 8260.46J.
- 10. COMMUNICATIONS: REMOVED DEPARTURE CONTROL (DEP CON) CHARTING DEPARTURE CONTROL FREQUENCY OCCURS AUTOMATICALLY PER IAW 8260.46J APPENDIX E.
- 11. AIRPORTS SERVED: UPDATED TO "AIRPORT ID" ONLY IAW 8260.46J.
- 12. CHANGED DP ROUTE DESCRIPTION FOR ALL RUNWAYS FROM "CLIMB HEADING" TO "CLIMB ON HEADING" IAW 8260.46J APPENDIX E.
- 13. ADDED "APT. ID" FOLLOWING THE AIRPORT NAME ON DP ROUTE DESCRIPTION, TAKEOFF MINIMUMS AND CONTROLLING OBSTACLES IAW 8260.46J.
- 14. MSA: ADDED "KCLT MSA FROM KCLT 3800; KJQF MSA FROM KJQF 3800; KAKH MSA FROM KAKH 3800; KEQY MSA FROM KEQY 3100; KIPJ MSA FROM KIPJ 3800; KLKR MSA FROM KLKR 2300; KVUJ MSA FROM KVUJ 3100; KRUQ MSA FROM KRUQ 3400; KUZA MSA FROM KUZA 3800" IAW 8260.46J APP E, SEC 1, PARA 2K AW 8260.46J, APPENDIX E (2) (K).
- 15. ADDITIONAL FLIGHT DATA: ADDED " AIRPORT MV: KCLT (P) 7W/2000, KJQF 6W/1995, KAKH 6W/2000, KEQY 6W/1990, KIPJ 6W/1995, KLKR 7W/2000, KVUJ 6W/1985, KRUQ 6W/1985, KUZA 5W/1990" CRITERIA CLARIFICATION MEMO (7/15/2022) TO MEMO 283 (6/2/2022).
- 16. COMMUNICATIONS: ADDED "CHART:" TO THE FREQUENCIES FOR EACH AIRPORT IAW 8260.46J APP. E, SEC 1, PARA 20.
- 17. REMARKS: REMOVED "LETTER OF APPROVAL FOR EQY, LKR, AND VUJ AIRPORTS NOT LOCATED WITHIN EXTENDED PNA REQUIRED AND ON FILE APPROVED BY AFS-400 5-20-16" NO LONGER REQUIRED.
- 18. COMMUNICATIONS: STANLY COUNTY (KVUJ) REMOVED "UNICOM" PER NFDD 42 REMOVED FROM ARP.
- 19. DP ROUTE DESCRIPTION: REPLACE ALL INSTANCES OF "EXPECT RADAR" TO "ON RADAR" IAW 8260.46J 2-1-1.G (2).
- 20. DP ROUTE DESCRIPTION: MID-CAROLINA RGNL (KRUQ) ADDED "TAKEOFF RWY 2: CLIMB ON HEADING ASSIGNED BY ATC, THENCE..." FORM UPDATED.

02/06/2024: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 05/12/2023. DP ROUTE DESCRIPTION:

- 1. CHANGED GASTONIA MUNI FROM KJQF TO KAKH.
- 2. CHANGED ROCK HILL/YORK CO/BRYANT FIELD FROM KIZA TO KUZA.



FEDERAL AVIATION ADMINISTRATION FLIGHT STANDARDS SERVICE DEPARTURE (DATA RECORD)

-							RE (DATA RECORD)			
DP NAME LILLS						NUMBER THREE	DP COMPUTER CODE	SUPERSEDED NUMBER TWO	DATED 01/03/19	ACTUAL EFFECTIVE DATE
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS	
RW18C (AER)	351338.63N/0805711.41W	N	-	-	-	-				
1260 MSL		-	-	VA	175.96	-			CG 500 FT/NM	TO 1260
		-	-	VM	175.96	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
RW18L (AER)	351329.05N/0805610.17W	N	-	-	-	-				
1260 MSL		-	-	VA	175.97	-			CG 500 FT/NM	TO 1260
		-	-	VM	175.97	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
RW18R (AER)	351331.02N/0805802.71W	N	-		-	-				
1260 MSL		-	-	VA	175.96	-			CG 500 FT/NM	TO 1260
		-	-	VM	193.00	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
RW36C (AER)	351159.97N/0805702.92W	N			_	-				
1260 MSL		-	-	VA	355.96	-			CG 500 FT/NM TO	D 1260
		-	-	VM	323.00	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
RW36L (AER)	351202.23N/0805755.07W	N	-	-	-	-				
1260 MSL		-	-	VA	355.96	-			CG 500 FT/NM T	O 1400

48
Page 1 of 2

DP NAME LILLS						NUMBER THREE	DP COMPUTER CODE LILLS3.LILLS	SUPERSEDED NUMB TWO	DATED 01/03/19	ACTUAL EFFECTIVE DATE
FIX/NAVAID	LAT/LONG	<u>C</u>	FO/FB	LEG TYPE	<u>TC</u>	DIST (NM)	ALTITUDE	SPEED	REMARKS	
		-	-	VM	308.00	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
DIMOCD (AED)	254202 45N/0005022 20W									
RW36R (AER)	351203.45N/0805602.82W	N	-	-	-	-				
1260 MSL		-	-	VA	355.97	-			CG 500 FT/NM T	O 1260
		-	-	VM	018.00	-				
LAMDE	345926.51N/0800907.34W	Υ	FB	DF	-	-				
LAMDE	345926.51N/0800907.34W	Υ	-	IF	-	-				
LILLS	345607.59N/0795548.73W	Υ	FB	TF	106.77	11.43				